

## PRO-STOP™ SHOCK ABSORBING LANYARDS - E4



**1340220C**  
**PRO-STOP™ SHOCK ABSORBING LANYARD**

Single-leg with self locking snap hooks at each end x 6 ft. (1.8m)

**1340221C** 4 ft. (1.2m) length



**1340230C**  
**PRO-STOP™ SHOCK ABSORBING LANYARD**

Single-leg with self locking snap hook and flat steel rebar hook x 6 ft. (1.8m)

**1340223C** 4 ft. (1.2m) length



**1340240C**  
**PRO-STOP™ 100% TIE-OFF SHOCK ABSORBING LANYARD**

Double-leg with self locking snap hooks at each end x 6 ft. (1.8m)

**1340225C** 4 ft. (1.2m) length



**1340250C**  
**PRO-STOP™ 100% TIE-OFF SHOCK ABSORBING LANYARD**

Double-leg with self locking snap hook and flat steel rebar hooks at leg ends x 6 ft. (1.8m)

**1340226C** 4 ft. (1.2m) length

## PRO™ ELASTIC SHOCK ABSORBING LANYARDS - E4



**1341101C**  
**PRO™ ELASTIC SHOCK ABSORBING LANYARD**

Single-leg with snap hooks at each end x 6 ft. (1.8m)

**1341102C** 4 ft. (1.2m) length



**1342101C**  
**PRO™ ELASTIC 100% TIE-OFF SHOCK ABSORBING LANYARD**

Double-leg with snap hooks at each end x 6 ft. (1.8m)

**1342102C** 4 ft. (1.2m) length



**1342125C**  
**PRO™ ELASTIC 100% TIE-OFF SHOCK ABSORBING LANYARD**

Double-leg with snap hook and flat steel rebar hooks at leg ends x 6 ft. (1.8m)

**1342102C** 4 ft. (1.2m) length

Every PRO™ lanyard features easy to use self locking snap hooks for added safety and security on the jobsite. The hooks also incorporate high strength, corrosion resistant materials for added durability and longevity.