

MSA, GENERAL EQUIPMENT AND VENTILATION

MSA cont.



FPK5™ Tie-Back Shock Absorbing Lanyard

- 5,000 lb gate strength in any direction allows the FPK5 Carabiner to be tied back directly to the lanyard
- Available in web or cable version
- Web version utilizes Monster-Edge™ Webbing with 12,000 lb minimum breaking strength
- Available in both single and twin leg configurations
- Meets OSHA regulations, ANSI A10.14 & ANSI Z359.1, and is CSA certified
- 6' length



Part No.	Vendor No.	Description	UOM /Each
1006706*	10047084	Tie-back lanyard, nylon web, snaphook on one end	^
1006707*	10047085	Twin leg tie-back lanyard, nylon web	—
1006708*	10047086	Tie-back lanyard, cable, snaphook on one end	—
1006709	10047087	Twin leg tie-back lanyard, cable, snaphook on center	—

*NOT FOR SALE IN CANADA

FP Diamond™ Expanyard Shock Absorbing Lanyard

- The FP Diamond raises the standard for shock absorbing lanyards with these exciting features:
- Elastic design reduces trip/snag hazards
 - 6' Diamond Expanyard contracts to 4.5'
 - Durable polyester sheath for increased abrasion and UV resistance
 - Pouchless design – lighter weight and more comfortable to wear
 - Available in both single and twin leg configurations
 - The Diamond Expanyard is also available in a 10', which contracts to 7'
 - Meets OSHA regulations, ANSI A10.14 & ANSI Z359.1, and is CSA certified



Part No.	Vendor No.	Description	UOM /Each
1006710	10045936	6' Diamond, polyester lanyard, HL2000	^
1006711	10045938	6' Diamond twin leg, polyester lanyard, HL2000	—
1006712	10047290	6' Diamond twin leg, polyester lanyard, Expanyard	—

Dyna-Brake® Shock Absorbing Lanyard

- Strong and durable
- Available in single or twin leg configurations
- Meets ANSI Z359.1, ANSI A10.14, and OSHA Regulations



Part No.	Vendor No.	Description	UOM /Each
0201833	501222	Adjustable	^
1001742	501226	Fixed	—
0201836	501562	Twin Leg, Adjustable	—

Expanyard™ Shock Absorbing Lanyard

- Stretches to 6' length
- When relaxed, stays close to user's body
- Available in single or twin leg configurations
- Meets ANSI Z359.1, ANSI A10.14, and OSHA Regulations



Part No.	Vendor No.	Hardware	UOM /Each
1001061	501572	RL20/RL20	^
1001062	501574	Twin Leg, RL20/(2) RL20	—

Aptura™ Self-Retracting Lanyards

- The MSA Aptura self-retracting lanyards (SRL) are fast-acting fall arresters that limit free-fall distance, deceleration distance and fall arrest forces while allowing the user freedom of movement. Meet ANSI Z359.1, ANSI A10.14, and applicable OSHA standards. Features include:
- 12' lifeline
 - HL2000 Snaphook lifeline connection



Part No.	Vendor No.	Description	UOM /Each
1006702*	10044228	Aptura LT12 w/ back D Connector SRL Connection	^
1006703*	10044229	Aptura LT12 w/ HL2000 Connection	—
1008470	10053560	Aptura 30' SRL	—

*NOT FOR SALE IN CANADA

Roofer's Compliance Kit

- This kit puts together all the tools needed to form a personal fall arrest system. Specially designed for those needing fall protection for compliance. The Kit includes:
- Vest style FP Pro Harness with Qwik-Fit™ chest and leg straps
 - Back D-ring
 - 25' vertical lifeline with shock absorber, robe grab, and roof anchor
 - Convenient packaging in the form of a handy 6 gallon bucket



Part No.	Vendor No.	Description	UOM /Each
1006700	10049751	Roofer's Kit	^

General Equipment and Ventilation

- Confined Space Kits with Lynx Rescuer allow for non-entry rescue of a confined space entrant.
- Tripod Kits allow for great portability
- Kit includes:**
 - Lynx 8' Tripod (MSA# 10020050)
 - Lynx Rescuer 16m (MSA# 10011744)
 - Lynx Rescuer Mounting Bracket for Tripod (MSA# 506232)
 - Split Mount Pulley (MSA# 506222)
 - Tripod Carrying Bag 8' (MSA#507149)
 - Lynx Rescuer carrying bag (MSA# 507151)
 - Confined Space Training Video (MSA# 10007825)



Part No.	Vendor No.	Description	UOM /Each
1003692	10023966	with Lynx Tripod	^

ALLEGRO®

I N D U S T R I E S

Manhole Guard Rail


Designed to protect an area 33" x 33", this 42" high guard rail collapses to only 32" square x 4" for easy storage. Weighing 37 lbs., the strong, one inch tubular .078 gauge steel construction is powder-coated in safety yellow for a durable finish and high visibility. Simple one-piece construction offers easy, no-tools assembly. Rail locks open and two hooking chains provide protected entry and exit. For safety, the rail accommodates signs, flags or lights. For convenience, it can be used with a guard rail tent, umbrellas or winch.



Part No.	Vendor No.	Description	UOM /Each
1001322	9401	Manhole Guard Rail	^

Manhole Lid Lifter

The toughest manholes covers are easy to move with this one piece lifter. It features a long all-steel handle that provides the leverage necessary to lift the heaviest lids. For safe storage, the alloy steel hook recesses and locks into the pole. Rubber grips on the handle and foot prevent slips and cadmium-plating fights rust. 42" long, 9 lbs.



Part No.	Vendor No.	Description	UOM /Each
1001324	9401-20	Manhole Lid Lifter	^

Fall Protection & Confined Space Equip.