

G-Rail System

GUARDIAN
FALL PROTECTION



15181/15182/15183

Compliant with all OSHA 1910 and OSHA 1926 Subpart M regulations.

Custom configurations not available. Not repairable.
Contact customer service for details.

ALWAYS assemble and use G-Rail System according to instructions provided with equipment by the manufacturer.

G-Rail System is suitable for the following application:



Fall Prevention: G-Rail System may be used in Fall Prevention applications ONLY. Fall Prevention Systems are placed around the leading edges of any and all fall hazards to prevent a worker from going over an edge, and may be used in substitute of Fall Protection or safety netting systems. Installation requirements for G-Rail System set forth in product instruction manual MUST be adhered to. Personal Fall Arrest, Work Positioning, Climbing, Rescue, and any other systems must NEVER be connected to Fall Prevention Systems.

Materials: powder-coated steel or galvanized steel.

Toeboards must be 2" x 4" construction grade lumber. Baseplates must be at least 24" from the edge of any opening or leading edge hazard.

An outrigger is a guardrail installed perpendicular to a continuous run. ALWAYS use outriggers at BOTH ends of any interruption in a G-Rail System, and at BOTH ends of a continuous G-Rail System. There is no limit on the maximum length of a continuous G-Rail System.

UPC-A Codes:

15178: 672421151786
15180: 672421151809
15181: 672421151816
15182: 672421151823
15183: 672421151830
15184: 672421151847
15185: 672421151854



15178



15180



15184/15185

Part #	Size	Description
15178	21½"W x 21½"L	QuickSet Multi-Directional Baseplate
15180	10"W x 30"L	Baseplate
15181	42"H x 10'L	Guardrail
15182	42"H x 8'L	Guardrail
15183	42"H x 6'L	Guardrail
15184	10"L	Short Toeboard Attachment
15185	22"L	Long Toeboard Attachment