



Watch Dog® Lift Away Smooth Surface Graffiti Remover

Tech Data Sheet

Product Description & Use: Watch Dog® Lift Away Smooth Surface Graffiti Remover is a water base formulation which is biodegradable. Watch Dog® Lift Away Smooth Surface Graffiti Remover will remove most types of graffiti and many stains from previously unpainted non-porous surfaces. Watch Dog® Lift Away Smooth Surface Graffiti Remover has a low odor and is formulated to work in less than 1 min.

Features & Benefits:

- Water based
- Low odor
- Fast acting
- Aerosol application available
- Biodegradable

Limitations: Not recommended for use on vinyl, plastics, drywall, rubber, cars or trucks, some fiberglass, and previously painted or stained surfaces. Not recommended for use in temperatures below 40° degrees Fahrenheit. Always do a test patch prior to full removal.

Test Patch: Always perform a small inconspicuous test area on each type of substrate and paint coating prior to full application. Testing before beginning any project is the best way to ensure product effectiveness. Test patches can determine the proper dwell time and thickness to apply the product for your specific application. Failure to do a test patch can result in need for more than one application, increasing labor and material costs.

Recommended Substrates: Before applying to the entire substrate always do a test patch. Recommended for use on masonry, brick, metal, glass, wood, and concrete that is previously unpainted or stained.

Regulatory Information: VOC Compliance - Watch Dog® Lift Away Smooth Surface Graffiti Remover meets national, state and local regulations.

Preparation: Make sure surface is clean, dry and free from any debris.

Surface and Air Temperatures: To avoid product from freezing and reducing effectiveness do not use below 35° degrees Fahrenheit. For best results, use product in temperatures above 50° degrees Fahrenheit and below 90° degrees Fahrenheit. Product effectiveness is increased in warmer temperatures.

Application & Spread Rate: Apply product liberally, at full strength using a brush or roller. Aerosol version may be sprayed. Allow product to remain on surface for no longer than a minute. Product may require some agitation with a nylon bristled brush or Scotch™ Brite pad. **Watch Dog® Lift Away Smooth Surface Graffiti Remover** provides an average spread rate of approximately 100-125 sq. ft. per. gallon; results may vary based on the substrate texture and porosity.

Spray Application: Not recommended for spray application, however there is an aerosol can version.

Removal & Clean Up: Rinse product from the surface with a garden hose. Dispose of water and waste according to federal, state and local regulations.

Best Practices:

- Always test each type of surface and coating for efficacy, dwell times may vary.
- Do not leave the surface unattended after application as this product works in under a minute and may cause damage to the underlying surface.

Availability & Cost: **Dumond® Chemicals** products are available through a nationwide network of paint stores, hardware stores and safety supply distributors. For outlet nearest you please visit www.dumondchemicals.com once on the website type your zip code or postal code into the dealer locator to find addresses and phone numbers of your nearest dealer.

Health & Safety Requirements: Not for internal consumption. While **Watch Dog® Lift Away Smooth Surface Graffiti Remover** is formulated to be safe for the user, surface and environment, proper safety procedures should be followed at all times when handling this product. Read the full label and MSDS for precautionary instructions before use.

24-Hour Emergency Information:

1-800-535-5053 **North America** or 1-325-323-3500 **International**

Warranty: **Dumond® Chemicals, Inc.** warrants all of its products to be free from defects, and makes no other warranties with respect to its products, express or implied, including without limitation the implied warranties of MERCHANTABILITY OF FITNESS FOR PARTICULAR PURPOSE. **Dumond® Chemicals, Inc.** liability shall be limited in all

Events to supplying sufficient products to re-treat the specific areas to which defective product have been applied. **Dumond® Chemicals, Inc.** shall have no other liability, including liability for incidental, consequential or resultant damages whether due to breach of warranty or negligence. This warranty may not be modified or extended by representatives of **Dumond® Chemicals, Inc.** or its distributors, and dealers.

Technical Services: Dumond's expert staff is available to answer technical questions and provide product-specific information. On-site assistance is available at no additional cost. Call 800-245-1191, email info@dumondglobal.com or visit www.dumondchemicals.com with product or technical questions.

Technical Data:

- **Form** - White Liquid
- **Wt./Gal** – 10lbs/gal
- **Flash Point** - 146
- **pH** - 10
- **VOC** - 0
- **Freeze Point** - 32
- **Shelf Life** - 3 Years



83 General Warren Blvd, Suite 190 Phone: 609/655-7700 email: info@dumondglobal.com
Malvern, PA 19355 Fax: 609/655-7725 www.dumondchemicals.com