

## IBIX | 40 H<sub>2</sub>O

IBIX® 40 features dual action wet and/or dry technology designed for hard to reach workspaces. Perfect for a wide variety of applications, pre-paint preparation and surface cleaning, the IBIXPro40 delivers a perfectly consistent air and media flow and notably requires only one operator and can be run by most small compressors. Minimal dusting protects the health and safety of the operator and environment. IBIX provides the ultimate power in a small package.

- ▶ **Includes Application Gun and Water Nozzle**
- ▶ **Filling Funnel w/Sieve**
- ▶ **Cleans steel, aluminum, stainless steel, wood, glass, marble, concrete, masonry, stone, composite materials, etc.**



**Adjustable Air Flow**



**VORTEX Technology**



**IBIX 9 Nozzle Kit**

**IBIX Systems designed for Multiple Green Abrasives.**  
(Garnet, Calcium, Glass, Walnut and other)

### PRODUCT SPECIFICATIONS

Nozzle	Pressure	58 PSI - (4 bar)	72.5 PSI - (5 bar)	87 PSI - (6 bar)	101.5 PSI - (7 bar)	116 PSI - (8 bar)
Standard 13/32" (10 mm)		139 cfm	153 cfm	167 cfm	183 cfm	195 cfm
<b>Also available for this system</b>						
Size 9/32" (7 mm)		80 cfm	88 cfm	95 cfm	101 cfm	107 cfm
Size 5/16" (8 mm)		90 cfm	98 cfm	107 cfm	117 cfm	125 cfm
Size 15/32" (12 mm)		200 cfm	220 cfm	240 cfm	264 cfm	280 cfm

Item	Description
1652-5711	IBIX 40 H2O Wet/Dry Surface Prep System
<b>Accessories</b>	
I25-NK	IBIX 9 Nozzle Kit

Pressure adjustable:	3 - 123 PSI (0.2 - 8 bars)
Abrasive range:	30-350 Mesh (2.5 - 0.025 mm)
Hose length:	30 ft. (10 m)
Standard nozzle size:	13/32" (10 mm)
Tank capacity:	10.5 gal. / 1.4 ft <sup>3</sup> / 84 lbs (40 liter)

Usage rate:	2-3 lbs./sq. ft. avg.
Performance:	75-150 sq. ft./h avg.
System height (w/out handle):	29"
System width (w/out front legs):	18" (w/legs 14")
Packaging (box) dimensions:	21"x25"x37"
Machine net weight (empty tank):	98 lbs. (44.5 kg)

**Locations Nationwide**  
Visit [www.aramsco.com](http://www.aramsco.com)  
to find a branch nearest you.