

ULTRA-LOK®

SELF RETRACTING LIFELINE (SRL)

Designed for
maximum
durability
and minimal
weight



Type 2 Ultra-lok® Self Retracting Lifeline!

3103107 - Ultra-Lok® 3.4m Web, Self Retracting Lifeline

- Stainless steel working components for corrosion resistance
- Webbing lifeline for reduced weight
- Self adjusting disc brake for reliability
- Built in anti-ratcheting capabilities
- Reserve lifeline retention system for added safety
- Audible indicator ensures the breaking system is functioning properly
- Self-locking swivel double action snap hook with visual impact indicator
- Swivelling anchorage loop to prevent twisting of lifeline
- Internal energy absorption system
- Meets or exceeds all applicable industry standards

PRODUCT NEWS



Call **1800 245 002 (AUS)**
0800 212 505 (NZ)

Head Office and Manufacturing
20 Fariola Street Silverwater NSW 2128 Australia
Phone: +61 2 9748 0335 Fax: +61 2 9748 0336
Email: sales@capitalsafety.com.au www.sala.com.au
DBI-SALA is a brand of Capital Safety



ULTRA-LOK®

SELF RETRACTING LIFELINES (SRL'S)

Self Retracting Lifeline's DBI-SALA were the first to develop SRL's and they are still the most popular product of their kind. SRL's extend and retract automatically, letting you comfortably move about at your normal speed within a recommended working area while operating at peak efficiency. For ease of use and worker acceptance, our SRL's are the lightest in the industry.

Ultra-Lok® Self Retracting Lifelines DBI-SALA's Ultra-Lok® SRL's are manufactured with a durable reinforced urethane housing, either a 5mm wire rope, 6mm spectra synthetic rope or 25mm webbing lifeline and aluminium side plates for maximum durability and minimum weight. For added security, Ultra-Lok® SRL's have an anti-ratcheting twin disc brake system with an audio indicator to let you know it is functioning properly.

Ultra-Lok® Series SRL's The Ultra-Lok® series is designed to provide fall protection in a range of industries and environments. They are spring tensioned for normal work motions. If you slip or fall, the sudden jerk in the cable/webbing activates the braking mechanisms and brings the user to a stop. They are ideal for: inspection, general construction and maintenance work and confined space applications. DBI-SALA's Ultra-Lok® Series SRL's are available in galvanised, stainless, spectra synthetic rope and webbing lifelines as outlined in the specifications table.

Specifications: Ultra-lok® Webbing and Cable SRL's

Part Number	Length	Snap Hook	Weight	Lifeline	
3103107	3.4m	H250	1.9kg	25mm wide webbing	-
3103207	6.0m	H250	2.7kg	25mm wide webbing	-
3504433*	6.0m	H250 Swivel	4.1kg	5mm Galvanised	Stainless (3504437)
3504430*	10m	H250 Swivel	5.0kg	5mm Galvanised	Stainless (3504432)
3504450*	15m	H250 Swivel	6.8kg	5mm Galvanised	Stainless (3504452)

*Also available in Spectra Synthetic Rope

Pawls	Stainless Steel
Main Shaft	Stainless Steel
Motor Spring	Stainless Steel
Size Housing	3103107; 194mm length x 133mm width x 51mm height 3103207; 226mm length x 162mm width x 75mm height 3504433; 294mm length x 152mm width x 85mm height 3504430; 294mm length x 152mm width x 85mm height 3504450; 321mm length x 202mm width x 93mm height
Drum	Webbing style - Nylon, Cable style - Aluminium
Side Plates	Aluminium
Housing	Webbing style - Glass reinforced urethane, Cable style - Reinforced urethane
Finish	Webbing style - Custom mould colour/anodised, Cable style - Anodised aluminium components
Snap Hook	Double action, 19mm gate opening, alloy steel, 22kN resistance
Capacity	141kg (190kg for 3103107 model)
Compatibility	Designed for use with DBI-SALA approved harnesses, components or systems or as recommended by a competent person
Maximum Arresting Distance	1.1m
Maximum Arresting Force	4kN
Standards	Exceeds OSHA, ANSI Z359.1-1991, ANSI A10.14-1991, EN360 & AS/NZS 1891.3
Country of Origin	United States

Special Instructions / Conditions of Use

Reading user instruction manual prior to use is essential

ISO 9001 - With a full quality assurance program certified under ISO 9001, DBI-SALA supplies the industry with a quality range of safety products to provide added security. That's why we back each of our fall protection and rescue systems with the best training, technical assistance and customer service in the business. It makes life easier for you and safer for your workers.



**Call 1800 245 002 (AUS)
0800 212 505 (NZ)**

Head Office and Manufacturing
20 Fariola Street Silverwater NSW 2128 Australia
Phone: +61 2 9748 0335 Fax: +61 2 9748 0336
Email: sales@capitalsafety.com.au www.sala.com.au
DBI-SALA is a brand of Capital Safety



DATA SHEET