

MSA Supreme Pro™ Ear Muff

SUPREME PRO



Sound Control™ Electronic Hearing Protection

The MSA Supreme Pro™ Ear Muff gives police officers, military personnel, and hunters optimum hearing protection, along with the ability to hear the surrounding environment. Especially useful for target shooting, the Supreme Pro Ear Muff's ear cups are shaped to suit both right- and left-handed shooters. Other features include AUX input and watertight battery compartment.

- Two separate, well-shielded microphones for optimum stereo effect sound direction location
- High amplification and natural sound reproduction without chopping or cutting out
- Approximate battery life of 600 hours, using two standard AAA batteries
- AUX input for connecting external audio sources, such as radio
- Lead with 3.5mm mono jack plug included

Ordering Information:

Headband model 10061285
 Neckband model 10079966
 Hygiene kit 10061224

Note: This Bulletin contains only a general description of the products shown. While uses and performance capabilities are described, under no circumstances shall the products be used by untrained or unqualified individuals and not until the product instructions including any warnings or cautions provided have been thoroughly read and understood. Only they contain the complete and detailed information concerning proper use and care of these products.



Corporate Headquarters
 P.O. Box 426, Pittsburgh, PA 15230
 USA
 Phone 412-967-3000
www.MSAnet.com
U.S. Customer Service Center
 Phone 1-800-MSA-2222
 Fax 1-800-967-0398

MSA Canada
 Phone 416-620-4225
 Fax 416-620-9697

MSA Mexico
 Phone 52-55 21 22 5770
 Fax 52-55 5359 4330

MSA International
 Phone 412-967-3354
 FAX 412-967-3451



Headband Version



Neckband Version

Headband Version: NRR=18dB

ANSI S3.19-1974 Data

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000
Mean	11	17	23	25	30	34	36	38	39
Stand. dev. (dB)	2.6	3.0	3.2	2.8	4.1	3.1	3.6	4.0	3.2

Neckband Version: NRR=19dB

ANSI S3.19-1974 Data

Frequency (Hz)	125	250	500	1000	2000	3150	4000	6300	8000
Mean	14.7	17.2	24.3	23.5	27.3	34.7	38.5	41.5	41.7
Stand. dev. (dB)	3.7	2.1	2.9	2.5	2.6	2.8	3.7	1.6	2.5

Noise Reduction Rating (NRR) is third-party certified in accordance with ANSI S3.19-1974, and meets CSA Class B.

