



Clean-Walk Framed Mats

5840 Series

Technical Data

November, 2010

Product Description

3M™ Clean-Walk Framed Mats 5840 Series feature a non-skid plastic base with a pad comprised of a multi-sheeted adhesive system that removes dirt and contaminants from shoe soles, wheels and other passing objects on contact. The pad offers 60 removable adhesive polyethylene sheets that lock dirt in place until discarded.

Construction

Backing	Adhesive	Color	Standard Mat Size
Frame – rigid polystyrene w/non-skid backing	N/A	White or Black	31.5 in. x 25.5 in. (80 cm x 64 cm)
Pad – polyethylene film	Acrylic	Transparent sheets on white bottom sheet	30 in. x 24 in. (76 cm x 61 cm)

Typical Physical Properties

Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

	ASTM Test Method
Thickness:	
3M™ Clean-Walk Framed Mat 5840 (frame with pad)	0.29 in. (7.3 mm) nominal D-3652
3M™ Clean-Walk Replacement Pad 5842	0.097 in. (2.4 mm) nominal
Temperature Use Range:	50°F to 100°F (10°C to 38°C)

Features

- Non-skid polystyrene backing (framed mat) stays securely in place and is ideal for use on carpeted surfaces.
- Framed mat is completely portable and reusable, simply adhere a 3M™ Clean-Walk Replacement Pad 5842.
- Removable adhesive sheets hold dirt securely until discarded to help provide a cleaner work environment.
- Individually tabbed and numbered sheets remove quickly and easily, exposing a clean sheet ready for immediate use.
- Numbered sheets help ensure one sheet removal and identify the number of remaining applications.
- Low profile construction reduces the risk of workers tripping and allows free movement of foot or wheel traffic.
- Unlike beveled edged products, edge remains clean during use.
- Helps extend the life of floor and carpeted surfaces by reducing the amount of contamination caused by foot traffic.

3M™ Clean-Walk Framed Mats

5840 Series

Application Ideas	<ul style="list-style-type: none">• For use in industrial settings to prevent contamination between high traffic production areas and office environments.• Ideal for fabricated metal shops, machinery and electronics equipment operations, printing and publishing facilities, construction and remodeling projects, health care facilities, warehouses, office, commercial and government buildings.• For use in clean room entrances.• Perfect for use with other non-adhesive mats for a complete mat protection program.
--------------------------	--

Application Techniques	<ul style="list-style-type: none">• Apply to a clean surface free of dirt, oil and other contaminants.• Not intended for outdoor use or use in areas with excessive moisture or direct sunlight.
-------------------------------	---

Storage	Store under normal conditions of 60°F to 80°F (16°C to 27°C) and 40 to 60% R.H. in the original carton.
----------------	---

Shelf Life	To obtain best performance, use this product within 12 months from date of manufacture.
-------------------	---

Technical Information	The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.
------------------------------	--

Product Use	Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.
--------------------	--

Warranty, Limited Remedy, and Disclaimer	Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.
---	---

Limitation of Liability	Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.
--------------------------------	--



Industrial Adhesives and Tapes Division

3M Center, Building 225-3S-06
St. Paul, MN 55144-1000
800-362-3550 • 877-369-2923 (Fax)
www.3M.com/industrial



Recycled Paper
40% pre-consumer
10% post-consumer

3M is a trademark of 3M Company.
Printed in U.S.A.
©3M 2010 70-0709-5278-6 (11/10)