

# STOCK VACUUM HOSE

Hose type	Hose Diameters	Description	1 1/2" Hose Weight oz/foot	Stock Lengths (Feet)
TV	1 1/4", 1 1/2"	Economical, smooth bore, flexible, commercial and residential	3.2	10, 25, 50
GT	1 1/2", 2"	Highly flexible, industrial light duty, clear	3.7	10, 15, 25, 50, 100
R	1 1/4", 1 1/2", 2"	Flexible, medium commercial duty, lightweight, most durable Polyethylene hose	4.5	10, 15, 25, 50
N	1 1/2", 1 1/4"	Extremely flexible, medium industrial duty, spring steel helix, reinforced with synthetic yarn, economical	5.1	10, 25, 30, 50
ESC	1 1/4", 1 1/2", 2"	Static conductive, heavy duty, carbon black / polyethylene resin blend provides permanent surface conductivity	6.5	10, 15, 25, 50

Hoses are available with and without hose cuffs. For additional diameters and hose types please call.

## VACUUM AND DUST HOSE SELECTION CHART

Hose Type	GT	N	R	TV	ESC
Dry	X	X	X	X	X
Wet		X	X	X	X
Asbestos Removal	X		X		
Carpet Extraction Portable		X	X		
Clean Room		X	X	X	
Concrete Dust			X		
Duct Vents		X			
Dust Collection Ducts		X	X	X	
Industrial Central Vacuums			X		X
Lead Paint Dust	X	X	X	X	X
Light Weight		X		X	
Marine Duty			X	X	
Material Handling Dry	X				
Oil Resistance	X				
Power Tools Portable		X	X	X	
Smooth Interior	X				
Static Conductive					X
Vacuum Commercial Portable		X	X	X	
Vacuum Industrial Portable			X		
Vacuum Shop Type		X	X	X	
Woodworking		X	X	X	
Hose Type	GT	N	R	TV	ESC
Wt oz/ft (1 1/2" hose)	3.7	5.1	4.5	3.2	6.5
Temp Range	-4 +150	-20 +150	-20 +140	-20 +140	-20 +140



T: (414) 962-5323 (877) 532-5323  
 F: (414) 962-7003  
 cservice@esca-tech.com

www.esca-tech.com