

Small Block Edge SRL

GUARDIAN
FALL PROTECTION
PERFORMANCE SAFETY GEAR

Part #	Length	Description
10900	11'	1" Nylon Webbing w/Carabiner, Swivel Top, & Snap Hook
10901	11'	1" Nylon Webbing w/Carabiner, Swivel Top, & Rebar Hook

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.14-12, and ANSI A10.32-2012 regulations.

Custom configurations available. Contact customer service for details.

Small Block Edge SRL is suitable for the following applications:



Personal Fall Arrest: Edge Series 11' SRLs may be used in Personal Fall Arrest applications as a component of a MAXIMUM 1 Personal Fall Arrest System (PFAS). Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. No free fall is permitted. SRL must always be positioned at or below anchorage connector. Applicable D-ring: Dorsal.



Restraint: Edge Series 11' SRLs may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.

For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-310 lbs., or up to 420 lbs. if deemed permissible by a Competent Person and used in combination with equipment explicitly certified for such use.

Materials: aluminum, galvanized steel, stainless steel, and zinc-plated steel.

NEVER for use in Leading Edge (LE) applications.

In Fall Arrest applications, anchorage connection point must always be at or above harness dorsal D-ring.

May be used in both mobile and stationary applications. For mobile applications, attach SRL carabiner to harness Dorsal D-ring, and attach snap hook to selected anchorage connector. For stationary applications, attach SRL carabiner to selected anchorage connector, and attach snap hook to applicable harness D-ring.

MAXIMUM 1 user per Small Block Edge SRL.

UPC-A Codes:

10900: 6 7242110900 8

10901: 6 7242110901 5

Packing Dimensions: 8--1/4"L x 8"W x 3"H.

Weight: 4--1/2 lbs. per unit.

Quantity: 100 per pallet; 490 lbs. total.



Repairable by the manufacturer. Contact customer service for details.