6280 Commander

HYDRAULIC WALK-BEHIND SCRAPER

FEATURES

The 6280 removes the worst of today's soft goods; such as glued-down floors, gummy commercial carpet, VCT, sheet vinyl, rubber tile, linoleum, indoor and outdoor sport surfaces, roofing material, and more. Its compact design makes it ideal for use in confined spaces, while the side slide weights add extra head pressure when forward and improved traction when moved over the back wheels.

A. Ergonomically designed, adjustable-position hand grips; hydraulic forward drive; self-propelled reverse drive; variable speed 10 to 45 feet per minute; manual drive system for throttle/speed control and smooth transitions

B. Six handle positions for work under counters and other confined areas; collapses to save space during transport and storage

C. Self-contained, limited-maintenance hydraulic fluid

D. Tie-down bail

E. Secure-mount side slide weights adjust scraper-head pressure; slide the weights back to increase weight over travel wheels

F. New rounded front weight design better deflects loose material during use

G. Adjustable, self-cleaning, industrial-grade wheels disengage for easy maneuvering

H. Motor equipped with thermal-overload-protection circuit breaker cord to eliminate unnecessary strain

I. Oscillating action rotates the cutting blade to cut through a range of materials over various substrates; extends life cycle of machine while reducing maintenance costs

J. New transport-wheel rack hanger on back of 6280 redesign

6280 SPECIFICATIONS		
Width	17.75"	45 cm
Max. Height	46"	117 cm
Height (handle folded)	30"	76 cm
Max. Length	51"	130 cm
Length (handle folded)	29"	74 cm
Weight	425 lb	192.8 kg
Removable Weight	47 lb front, 43 lb side	22.2 kg front, 19.5 kg side
Weight (machine only)	335 lb	152 kg
Speed	10-45 ft/min	3.0-13.7 m/min
RPM	3450/2875	
Voltage	115/230	
Frequency	60/50 Hz	
HP	1.5	1.12 kW
Amps (full load)	13/7.5	

Meets the requirements of the Machine Directive 2006/42/EC and EMC Directive 2004/108/EC. It is CE marked.

Included with the 6280

- 6280-299: Front-wheel assembly
- 6254: 50-foot, 12-gauge extension cord
- 148: 5" x 6" standard blade
- 6258: 3" x 12" self-scoring blade
- 6286: 3" x 10" heavy-duty blade
- 7050-200: 3" x 6" premium blade
- 7050-202: 3" x 10" premium blade
- 6280-401B: 7/32 t-handle wrench
- 1009: Safety glasses
- Instruction manual
- One-year manufacturer's warranty on parts and labor

Aramsco®
A SAFEGUARD INDUSTRIAL COMPANY

800.767.6933
www.aramsco.com

6280HD Gladiator

HYDRAULIC WALK-BEHIND SCRAPER

FEATURES

The 6280HD removes the worst of today's hard and soft goods, such as ceramic tile, wood floors, thin-set, sheet vinyl, linoleum, and more. Its compact design makes it ideal for use in confined spaces, while the side slide weights add extra head pressure when forward and improved traction when moved over the back wheels.

A. Ergonomically designed, adjustable-position hand grips; hydraulic forward drive; self-propelled reverse drive; variable speed 10 to 30 feet per minute; optional manual drive with removal of drive pins; system for throttle/speed control and smooth transitions

B. Six handle positions for work under racks and in other confined areas; collapses to save space during transport and storage

C. Self-contained, limited-maintenance hydraulic fluid

D. Tie-down bail

E. Secure-mount side slide weights adjust scraper-head pressure; side slide weights add extra head-pressure when forward and improved traction when moved over the back wheels

F. New rounded front-weight design better deflects loose material during use

G. Adjustable, self-cleaning, industrial-grade wheels disengage by clip-pin removal for easy non-powered maneuvering

H. Motor equipped with thermal-overload protection circuit breaker to eliminate unnecessary strain and electrical overload

I. Oscillating action rotates the cutting blade to cut through a range of materials over various substrates; extends life cycle of machine while reducing maintenance costs

J. New design incorporates nine isolators for the toughest jobs

6280HD SPECIFICATIONS		
Width	17.75"	45 cm
Max. Height	46.75"	119 cm
Height (handle folded)	29.75"	76 cm
Max. Length	49.5"	126 cm
Length (handle folded)	29.5"	75 cm
Weight	490 lb	222.3 kg
Removable Weight	78 lb front, 43 lb side	35.4 kg front, 19.5 kg side
Weight (machine only)	369 lb	167.4 kg
Speed	up to 30 ft/min	9.1 m/min
RPM	1725/1438	
Voltage	115/230	
Frequency	60/50 Hz	
HP	1.5	1.12 kW
Amps (full load)	14.7/10.5	

Meets the requirements of the Machine Directive 2006/42/EC and EMC Directive 2004/108/EC. It is CE marked.

Included with the 6280HD

- 6254: 50-foot, 12-gauge extension cord
- 6258: 3" x 12" self-scoring blade
- 6276-BU: 3" x 10" heavy-duty, self-scoring blade
- 6280HD-250: Transport-wheel assembly
- 7050-200: 3" x 6" premium blade
- 7050-202: 3" x 10" premium blade
- 7050-203: 3" x 12" premium blade
- 7050-204: 3" x 14" premium blade
- 6280-401B: 7/32 t-handle wrench
- 402276: 9-degree angle attachment
- 7280-2C: 30-degree angle attachment
- 7280-6: 6-inch cutting head
- 7280-12: 12-inch cutting head
- 7281-2: 2-inch carbide shank
- 7280-4: Retainer cap assembly
- 1009: Safety glasses
- Instruction manual
- One-year manufacturer's warranty on parts and labor