

HazMat Poly Blend Socks #YSO815 - 3" x 8', 15 socks/package



When hazardous liquids spill, use HazMat Sorbents for quick, efficient response. These poly blend-filled Socks contain and soak up acids, bases and unknown fluids fast.

- 100% poly blend-filled Socks quickly absorb nearly any type of caustic, hazardous or unknown liquid — including acids, bases, solvents and chemicals. Contain spills to keep fluids from spreading into larger areas and becoming slippery hazards. Color-coded Safety Yellow for fast identification; know exactly what you're reaching for in an emergency spill situation. Flexible to conform around the bases of leaky machines and offer a snug fit with no seepage. Note: Not compatible with sulfuric acid

YSO815 Specifications

Dimensions:	ext. dia. 3" x 8' L
Shipping	22" W x 24" L x 18.25" H
Dimensions:	
Sold as:	15 socks per package
Color:	Yellow Speckled Filler/Yellow Sleeve
Composition:	Poly Blend
Recycled Content:	100% Post-Industrial Recycled Poly Blend Filler
Absorbency:	Up to 25 gal. per package
Absorbency per:	Up to 1.7 gal. per sock
# per Pallet:	16
Incinerable:	Yes
Ship Class:	150

Metric Equivalent Specifications

Dimensions:	ext. dia. 7.6cm x 2.4m L
Shipping	55.9cm W x 61cm L x 46.4cm H
Dimensions:	
Absorbency:	Up to 94.6 L per package
Absorbency per:	Up to 6.4 L per sock

YSO815 Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Regulations and Compliance:

49 CFR 173.3(c)(2) - The area between a container and a salvage drum used for overpacking must have "sufficient cushioning and absorption material to prevent excessive movement of the damaged package and to eliminate the presence of any free liquid at the time the salvage drum is closed."

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

40 CFR 112.7(c)(1) - Facilities must have "appropriate containment and/or diversionary structures to prevent discharge oil from reaching a navigable water course."

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

Technical Documents:

(Available at spilltech.com)

Product Data Sheet (PDS)

Material Safety Data Sheet (MSDS)



SpillTech

Online:
spilltech.com

Phone:
1-800-228-3877 (N.Am.)
1-770-475-3877 (Other)

Fax:
1-800-872-3764 (N.Am.)
1-770-410-1812 (Other)

Email:
spilltech@spilltech.com