



Universal Poly Blend Pillows #GPIL818 - 8" x 18", 20 pillows/package



Use SpillTech® Universal Pillows to absorb high-volume leaks and spills of oils, coolants, solvents or water.

- **Pillows Absorb Fluids in Tight Spaces:** Pillows are easy to place in hard-to-reach areas — use under machines and leaky hydraulic hoses or wedge in corners cramped for space.
- **One Product for a Variety of Uses:** Pulls liquids from the floor like a sock. Catches leaks like a pan. Absorbs spills like a pad. It's one versatile product that works for many different jobs.
- **Absorb Large Quantities ... Quickly:** Ideal for spill response. Easy to toss into action. Pillow's large surface area speeds the absorption process and shortens the overall response time.
- **Color-Coded:** Color-coding helps you visually identify the right sorbent for your needs. Grunge-hiding Gray signifies universal sorbency for oils, coolants, solvents and water. Note: These items are not compatible with sulfuric acid.

GPIL818 Specifications

Dimensions:	8" W x 18" L
Shipping	24" W x 16" L x 11.5" H
Dimensions:	
Sold as:	20 pillows per package
Color:	Gray
Composition:	Poly Blend
Recycled Content:	100% Post-Industrial Recycled Poly Blend Filler
Absorbency:	Up to 23 gal. per package
Absorbency per:	Up to 1.15 gal. per pillow
# per Pallet:	35
Incinerable:	Yes
Ship Class:	150

Metric Equivalent Specifications

Dimensions:	20.3cm W x 45.7cm L
Shipping	61cm W x 40.6cm L x 29.2cm H
Dimensions:	
Absorbency:	Up to 87.1 L per package
Absorbency per:	Up to 4.4 L per pillow



Online:
spilltech.com

Phone:
1-800-228-3877 (N.Am.)
1-770-475-3877 (Other)

Fax:
1-800-872-3764 (N.Am.)
1-770-410-1812 (Other)

Email:
spilltech@spilltech.com

GPIL818 Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Regulations and Compliance:

49 CFR 173.3(c)(2) - The area between a container and a salvage drum used for overpacking must have "sufficient cushioning and absorption material to prevent excessive movement of the damaged package and to eliminate the presence of any free liquid at the time the salvage drum is closed."

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

40 CFR 112.7(c)(1) - Facilities must have "appropriate containment and/or diversionary structures to prevent discharge oil from reaching a navigable water course."

33 CFR 154.1047(c)(2) - Concerning navigation and navigable waters, a facility which handles, stores or transports Group V petroleum oils must identify response plan resources such as containment booms and other methods.

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

Technical Documents:

(Available at spilltech.com)

Product Data Sheet (PDS)

Material Safety Data Sheet (MSDS)

Chemical Compatibility (CCG)



Online:
spilltech.com

Phone:
1-800-228-3877 (N.Am.)
1-770-475-3877 (Other)

Fax:
1-800-872-3764 (N.Am.)
1-770-410-1812 (Other)

Email:
spilltech@spilltech.com