



## HazMat 95-Gallon Wheeled Spill Kit #SPKHZ-95-WD - Absorbs up to 84 Gallons



Be prepared for fast response with a SpillTech® HazMat Spill Kit!

- **Quick Response is Key:** Spills happen no matter how hard you try to avoid them. Forklifts knock over drums, tanks are punctured and transporters leak and drip. It is important to have the right sorbents on-hand when these spills occur to eliminate the slip-and-fall hazard. A quick response is the first order of business — and your best weapon — in the fight against spills. SpillTech® Spill Kits are packed with quality SpillTech® Products to help you clean up fast and comply with regulations.
- **The Sorbents You Need Are All Inside:** Includes a variety of sorbents to handle nearly any type of caustic, hazardous or unknown spill — including acids, bases, solvents and chemicals; pre-packed in an X-rated DOT-approved 95-Gallon OverPack. Self-contained Kit stores sorbent products for easy access as needed for spill control; saves time when quick response is necessary. Twist-on, double-wall lid with closed-cell gasket provides sealed and secure closure to protect sorbents from moisture, dirt and damage. Rust- and corrosion-free 100% polyethylene is durable to withstand rough handling. All-in-one design for easy maneuvering; two attached wheels and built-in handle mean no dolly or material handling equipment is needed.
- **Customized for You:** Don't see what you're looking for We can customize a Spill Kit to your exact specifications, including the container, its contents and accessories, with no upcharge! Contact your local Distributor for details.



Online:  
[spilltech.com](http://spilltech.com)

Phone:  
**1-800-228-3877 (N.Am.)**  
**1-770-475-3877 (Other)**

Fax:  
**1-800-872-3764 (N.Am.)**  
**1-770-410-1812 (Other)**

Email:  
[spilltech@spilltech.com](mailto:spilltech@spilltech.com)

## SPKHZ-95-WD Specifications

<b>Dimensions:</b>	ext. dia. 36" x 47" H
<b>Shipping</b>	36" W x 47" L x 36" H
<b>Dimensions:</b>	
<b>Sold as:</b>	1 per package
<b>Composition:</b>	N/A
<b>Absorbency:</b>	Up to 84 gal. per package
<b># per Pallet:</b>	1
<b>Incinerable:</b>	No
<b>Ship Class:</b>	150
<b>Includes:</b>	150 - 15" x 19" Yellow HazMat HeavyWeight SonicBonded Pads (YPB100H) 12 - 3" x 4' Yellow HazMat Sorbent Socks (YSO430) 6 - 3" x 8' Yellow HazMat Sorbent Socks (YSO815) 7 - 18" x 18" Yellow HazMat Sorbent Pillows (YPIL1818) 3 - 1 lb. Plug & Dike Epoxy Putty (A-PND) 2 - Pair Nitrile Gloves (A-GLV-NIT) 1 - Safety Goggles (A-GOG) 4 - 30" x 6" x 60" Yellow Disposal Bags & Ties (A-DISP BAG) 1 - Emergency Response GuideBook (A-EGB) 1 - 3" x 5" Vinyl Spill Kit Label (A-KIT LABEL) 1 - 32" dia x 47" Yellow 95-Gallon Wheeled OverPack (1H2/X113/S) (A95OVER-WD) 6 - 6" X 2" TamperProof Seals (A-SEAL)

## Metric Equivalent Specifications

<b>Dimensions:</b>	ext. dia. 91.4cm x 119.4cm H
<b>Shipping</b>	91.4cm W x 119.4cm L x 91.4cm H
<b>Dimensions:</b>	
<b>Absorbency:</b>	Up to 317.9 L per package



Online:  
[spilltech.com](http://spilltech.com)

Phone:  
**1-800-228-3877 (N.Am.)**  
**1-770-475-3877 (Other)**

Fax:  
**1-800-872-3764 (N.Am.)**  
**1-770-410-1812 (Other)**

Email:  
[spilltech@spilltech.com](mailto:spilltech@spilltech.com)

## SPKHZ-95-WD Technical Information

### Warnings & Restrictions:

There are no known warnings and restrictions for this product.

### Regulations and Compliance:

49 CFR 173.3(c)(1) - If a container of hazardous waste is damaged or leaking, it can be placed in a compatible salvage drum that meets UN criteria for shipping

40 CFR 263.31 - Transporters, "must clean up any hazardous waste discharge that occurs during transportation...so that the hazardous waste discharge no longer presents a hazard to human health or the environment."

40 CFR 263.30(a) - In the event of a spill, transporters must, "take appropriate immediate action to protect human health and the environment."

29 CFR 1910.1450(e) - OSHA requires containment and cleanup materials for spills in laboratories to reduce occupational exposure to hazardous chemicals.

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

### Technical Documents:

(Available at [spilltech.com](http://spilltech.com))

Product Data Sheet (PDS)



Online:  
[spilltech.com](http://spilltech.com)

Phone:  
**1-800-228-3877 (N.Am.)**  
**1-770-475-3877 (Other)**

Fax:  
**1-800-872-3764 (N.Am.)**  
**1-770-410-1812 (Other)**

Email:  
[spilltech@spilltech.com](mailto:spilltech@spilltech.com)