

IAQ 1000

Mold & Mildew Stain Remover

Product Description

8315

IAQ 1000 is a hydrogen peroxide based biodegradable, chlorine free cleaner. IAQ 1000 is pH-neutral, and contains an agent that will whiten and brighten while cleaning, but does not contain sodium hypochlorite (bleach). IAQ 1000 is suitable for use in water damage restoration situations to remove stains from mold, mildew and other microbial growth on porous, semi-porous, and non-porous materials. IAQ 1000 contains no dyes or perfumes, and is not corrosive like many industrial cleaners. IAQ 1000 is specifically designed for cleaning after water damage, sewer backups and floods. IAQ 1000 is supplied in a powerful, ready-to-use formula that can be applied directly from the container.

APPLICATION PROCEDURES

Application Information

Test textiles & fabrics for color stability in an inconspicuous area prior to use. Always take care to avoid skin and eye contact by using protective measures such as nitrile rubber gloves (or equivalent) and safety glasses.

WATER DAMAGE: IAQ 1000 is suitable for use in water damage restoration situations to remove odor causing bacteria on porous, semi-porous, and non-porous materials including: carpets, carpet cushion, sub floors, drywall, trim and frame lumber, tackless strip and paneling. When using IAQ 1000 undiluted, saturate affected materials with enough product to remain wet for at least 10 minutes. Use proper ventilation.

CARPETS, CARPET-CUSHIONS AND OTHER POROUS MATERIALS SUCH AS SUB FLOORS, DRYWALL, TRIM AND FRAME LUMBER, TACKLESS STRIP AND PANELING: For water damage from a clean water source, extract excess water. Test hidden area for colorfastness. Remove gross filth or heavy soil. Apply product directly with sprayer using a coarse spray tip to fully saturate affected materials. Agitate the IAQ 1000 solution and allow the materials to remain damp for 10 minutes. Follow with a thorough extraction. Dry rapidly and thoroughly.

SPECIAL INSTRUCTIONS FOR CLEANING CARPET: For use on wet cleanable synthetic fibers. Do not use on wool. Vacuum carpet thoroughly prior to cleaning. Test fabric for color fastness. For portable extraction units: Mix 1 part IAQ 1000 with 1 part water. For rotary floor machines: Mix 1 part IAQ 1000 with 1 part water and apply at the rate of 500-1000 sq. ft. per gallon. Do not mix this product with other cleaning products.

Follow the cleaning procedures specified by the manufacturer of the cleaning equipment. After using the product, set the carpet pile and protect the carpet from furniture legs and bases while drying. Do not over-wet. If applied to stain resistant nylon carpet, follow up by applying a fabric protector recommended by the carpet manufacturer.

PRECAUTIONS

EYE IRRITANT. MAY CAUSE SKIN IRRITATION WITH PROLONGED CONTACT. Avoid contact with eyes, skin and clothing. Wear nitrile gloves and safety glasses when handling. Do not take internally. Keep out of the reach of children.

EYE CONTACT: Flush immediately with plenty of water for at least 15 minutes and get medical attention.

SKIN CONTACT: Rinse thoroughly with water. Seek medical attention if irritation persists. Possible irritation and/or dying of skin from allergic reaction or prolonged contact.

INHALATION: Remove to fresh air.

INGESTION: Get medical attention immediately. Give large quantities of water or milk. Never give anything by mouth to an unconscious person. Do not induce vomiting!

STORAGE: Store in securely closed and upright in original container. Ventilated cap could leak if container is placed on side. Store in a dry place at temperatures between 40°F (4.5°C) and 90°F (32°C). Avoid shipping or storing below freezing, in sunlight, or above 90°F. If product freezes, thaw at room

Properties

Product Specifications

Active Ingredient:	Hydrogen Peroxide
Color:	Clear
Odor:	None
Foam:	0
Flash Point:	Non-combustible
pH:	6.5-7.5
Shelf Life:	12 Months Min.

(Original Sealed Container)

Available Package Sizes

5 gallon containers



Application Information

temperature and shake gently to remix components. Store in locked area inaccessible to children.

CAUTION!

KEEP OUT OF REACH OF CHILDREN.

Do not take internally. Close container after each use.

Keep from freezing.

Store between 40°F (4.5°C) and 90°F (32°C)

24 hour Emergency "CHEM-TEL" - 800.255.3924

Fiberlock Products and CPVC Compatibility

Manufacturers of chlorinated polyvinyl chloride ("CPVC") pipe believe that it can be sensitive to or incompatible with chemicals found in many commonly used household and industrial cleaning products, coatings, adhesives and other compounds, and that those chemicals can cause stress cracks or pipe failure. Fiberlock recommends that users always check pipe for markings that indicate the type of material it is made of and that users contact the pipe manufacturer directly before applying any Fiberlock products to CPVC pipe.

For Technical Information call 800.342.3755

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither Fiberlock Technologies, Inc., nor its agents shall be responsible for the use or results of use of this product or any injury, loss or damage, direct or consequential. We recommend that the prospective user determine the suitability of this product for each specific project and for the health and safety of personnel working in the area.

IAQ 1000, the IAQ 1000 Logo and other marks in this literature are trademarks of Fiberlock Technologies, Inc.

Fiberlock Technologies, Inc. • 150 Dascomb Rd • Andover, MA 01810 • www.fiberlock.com • 800.342.3755