

Universal SMF Roll #GRSMF100H-BX - 15" x 100', 1 roll/package



Rugged SurvivorSeries™ Mat Roll is strong for your toughest jobs. It survives the punishment of everyday wear and tear.

- **Built-in Layers for Long Lasting Reliability:** This innovative Mat features a SpunBond top layer that wicks liquids away into the MeltBlown core where it is trapped to keep the Mat and floors safe and dry. The bottom layer is built of densely woven strands of FineFiber to increase surface area, enabling the Mat to grip the floor and securing it for safer walking. All layers are ultrasonically bonded together for durability and resistance to wear in high traffic areas. Strong and long-wearing, SurvivorSeries™ Mat stays on the job so you use less and save money!
- **Versatile All-In-One Mat is a Roll, Pad and Sock:** One product is all you need! Use conveniently packaged All-in-One SurvivorSeries™ Mat Roll as a Roll, Pad or a Sock. Handy dispenser box keeps Mat clean and can be stored anywhere for easy access.
- **High Sorbency and Multi-Perforations:** Absorbs high volumes of liquid fast. Color-coding helps you visually identify the right sorbent for your needs. Grunge-hiding Gray signifies universal sorbency for oils, coolants, solvents and water. Roll is perforated every 3.75" vertically and every 17" horizontally for increased versatility.

GRSMF100H-BX Specifications

Dimensions:	15" W x 100' L
Shipping Dimensions:	13" W x 38" L x 13" H
Sold as:	1 roll per package
Color:	Gray
Composition:	Polypropylene
Absorbency:	Up to 18.9 gal. per package
# per Pallet:	30
Basis Weight:	HeavyWeight
Incinerable:	Yes
Ship Class:	150

Metric Equivalent Specifications

Dimensions:	38.1cm W x 30m L
Shipping Dimensions:	33cm W x 96.5cm L x 33cm H
Absorbency:	Up to 71.5 L per package

GRSMF100H-BX Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Regulations and Compliance:

49 CFR 173.3(c)(2) - The area between a container and a salvage drum used for overpacking must have "sufficient cushioning and absorption material to prevent excessive movement of the damaged package and to eliminate the presence of any free liquid at the time the salvage drum is closed."

29 CFR 1910.22(a)(2) - Floors in your workplace should be, "maintained in a clean and, so far as possible, a dry condition."

29 CFR 1910.1450(e) - OSHA requires containment and cleanup materials for spills in laboratories to reduce occupational exposure to hazardous chemicals.

29 CFR 1910.120(j)(1) - Under an OSHA requirement, "DOT-specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks, or ruptures may occur."

29 CFR 1910.107(g)(2) - OSHA requires spraying areas to be "kept as free from the accumulation of deposits of combustible residues as practical."

29 CFR 1910.107(b)(3) - If floors in a spray booth or work area are combustible, they "shall be covered with noncombustible material of such character as to facilitate the safe cleaning and removal of residues."

Technical Documents:

(Available at spilltech.com)

Product Data Sheet (PDS)

Material Safety Data Sheet (MSDS)

Chemical Compatibility (CCG)



SpillTech

Online:
spilltech.com

Phone:
1-800-228-3877 (N.Am.)
1-770-475-3877 (Other)

Fax:
1-800-872-3764 (N.Am.)
1-770-410-1812 (Other)

Email:
spilltech@spilltech.com