

# Phoenix AirMax

## Radial Air Mover

### At 925 CFM and 1.9 Amps - Best-in-Class

The Phoenix AirMax is the new leader in performance, convenience, portability, and safety for low profile air movers.

Its compact 20 1/2" X 17" footprint and 8 7/8" height make the Phoenix AirMax the most compact and portable fan in its class. The rugged molded in handle gives you the solid control required when packing and unpacking lots of air movers. Its easy-winding cord wrap and multiple securement options makes it a snap to prep for transport. Because of its deeply-molded interlocking features, the Phoenix AirMax is rock solid when stacked for transport.

With its Patent Pending, motor support x-bracket and optimized outlet shape, the Phoenix AirMax delivers airflow of 925 CFM. This gives you high velocity air over a 25% larger area than other low profile air movers. In addition, the Phoenix AirMax is stable in all 4 drying positions to maximize flexibility.

The Phoenix AirMax is the safest fan in its class providing a quality GFCI convenience receptacle that protects not only connected loads, but onboard components as well. This is unlike competing fans that require external GFCI protection. In addition, where competitors position high voltage electrical connections low to the floor, the leading edge design of the Phoenix AirMax allows these connections to be located more than 4 times the minimum required height. The Phoenix AirMax is built to keep the contractor and their customers safe.



Patent Pending



**Xactimate Code:**  
**WTRDRY**

### Features

- 925 CFM
- 1.9 Amps
- Onboard circuit breaker and branch protection GFCI
- Daisy chain up to 6 fans on a single 15 Amp circuit
- Ultra secure stacking and cord wrap
- Heavy wall polypropylene housing
- Cord 16ft Power Cord
- ETL Tested to UL and CSA Standards



Made in USA

[www.UsePhoenix.com](http://www.UsePhoenix.com)

innovative  
**DESIGN**

exceptional  
**VALUE**

proven™  
**PERFORMANCE**

## Phoenix AirMax

### Specifications

<b>Part No.</b>	4035000
<b>CFM</b>	925
<b>Cord</b>	16 ft Power Cord
<b>Outlet</b>	15A UL Rated GFCI Duplex Receptacle
<b>Current Draw</b>	1.9 Amps
<b>Voltage</b>	115 VAC
<b>Warranty</b>	Year One - 100% parts and labor (all components) Year Two - 100% parts only (all components) Year(s) Three through Seven - Materials and workmanship of the housing only.

### Dimensions

	Machine	Shipping
Width	17"	17 1/2"
Height	8 7/8"	9 1/4"
Depth	20 1/2"	21 1/8"
Weight	21 lbs	22 lbs

### Popular Accessories

4024936 Duct, Lay Flat, 14" x 250'

### Patent Pending

