

DIRECTIONS

Air Deodorization

Pre-test for safety of surface before fogging or spraying directly onto it. Cover or mask off all surfaces not compatible with the solvents in the solution. Mix 1 part solution with up to 4 parts water. Spray mixed solution onto treatment area. This solution may also be fogged using a U.L.V. wet fogger. Use the finest setting possible and repeat as necessary. Brushing solution in with natural bristle brush can assist penetration of soft surfaces. Wear a NIOSH approved N95 organic vapor respirator, gloves and goggles when fogging the treatment area. For fogging, area must be vacated of pets and unprotected people for 30 minutes after treatment.

Cleaning Additive to Remove Odors

For wall cleaning solution, use 3 ounces per diluted gallon. For water-based paint, use 4 ounces per gallon. For carpet and upholstery detergents, use 1 ounce per gallon to cut soot and deodorize wet cleanable textiles.



U.L.V. WET FOGGER

The compact & stable U.L.V. wet fogger is the best choice for open-area & sub-surface deodorizing & disinfecting with water-based deodorizers & disinfectants designed for fogging.



Eliminates skunk, cigarette smoke, urine odors and much more!

Available in Gallons and 4 x 1 gallon cases | Dilution Ration: 1-4 oz./gal.

OmniPro Manufacturing | 4282 South 590 West Salt Lake City, UT 84123 | 866-215-7591

