

## RESTORATION PRIMER & SEALER

### DESCRIPTION

Product No.: 3090

**RECON** Restoration Primer & Sealer is a high quality fast-drying pigmented shellac. It will seal smoke stains and odor caused by fire as well as knots and resin areas on all wood. This product may also be used as a bonding primer or as a general purpose fast dry primer on most surfaces. It prevents migrating or bleeding stains which show through other primers. Ideal for preparing restored surfaces prior to final refinishing.

### PROPERTIES

- **Weight per gallon:** 9.7 lbs.
- **Color:** White
- **Odor:** Alcohol
- **Finish:** Flat
- **Dry Time:** To touch-15 Min.  
To recoat-45 Min.
- **Coverage:**  
Smooth surfaces: 350-400 sq.ft./gal  
Porous surfaces: 100-150 sq.ft./gal
- **Packaged:** 1-gallon (4/case)

## APPLICATION INFORMATION

### SURFACE PREPARATION

Surfaces to be coated must be free of dust, mildew, mold, dirt, grease, loose paint, oil, glue, size, calcimine, wax, soap and other contamination to ensure adhesion. Clean mold-contaminated surfaces with an EPA-registered antimicrobial cleaner. Patch any irregularities with an appropriate patching compound.

**Smoke/Fire Damage:** Clean surfaces with appropriate RECON cleaning & restoration products. Spot prime or full prime with RECON Restoration Primer & Sealer as necessary to seal stains & odors.

**Plaster-** Knife off all nubs and protrusions. Wipe with a clean damp cloth to remove loose particles. Do not sand new plaster until it is primed.

**Wallboard, Sheetrock, Gypsum Board-** Joint cement should be sanded smooth, but avoid abrading the paper.

**Wood-** Seal knots and stains with RECON Restoration Primer & Sealer then prime with acrylic or alkyd enamel undercoat. Weathered or unsound wood should be sanded to paintable surface.

**Previously Painted Surfaces-** Wash, sand or dust to obtain a paintable surface. (OVER)

**Glossy Surfaces-** Dull by sanding to insure proper adhesion of paint.



# **RECON™**

## **RESTORATION PRIMER & SEALER**

### **PRECAUTIONS**

**FLAMMABLE.** Do not mix with water, oils, other paint types. Do not apply when air or surface temperature is below 40°F or when drying conditions are poor. Do not apply when rain, fog or dew is imminent. Do not use on large exterior areas or dimensionally unstable exterior wood such as siding. Spot touch the necessary areas only. Highly alkaline acoustical finishes applied over this primer may result in brown staining.

**EYE IRRITANT. MAY CAUSE SKIN IRRITATION WITH PROLONGED CONTACT.** Avoid contact with eyes, skin and clothing. Do not take internally. Keep away from heat, sparks and flame. Use only with adequate ventilation. Keep out of the reach of children. Close container after each use. Read and understand the Material Safety Data Sheet (MSDS) before using this product.

### **FIRST AID**

**EYE CONTACT:** Immediately flush eyes with water for no less than 15 minutes. Seek medical attention if irritation persists.

**SKIN CONTACT:** Flush with clean water followed by washing with mild soap and water. Seek medical attention if irritation develops.

**INGESTION:** Immediately drink 2 glasses of water. Do not induce vomiting. Seek medical attention immediately.

**KEEP FROM FREEZING  
FOR PROFESSIONAL USE ONLY  
KEEP OUT OF REACH OF CHILDREN  
DO NOT TAKE INTERNALLY  
FLAMMABLE!**

<b>HMIS RATING</b>	
<b>Health</b>	<b>1</b>
<b>Flammability</b>	<b>3</b>
<b>Physical Hazard</b>	<b>1</b>
<b>Personal Protection</b>	<b>B</b>

**DISCLAIMER:** These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither Fiberlock Technologies, Inc., nor its agents shall be responsible for the use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability of RECON Restoration Primer & Sealer for each specific project and for the health and safety of personnel working in the area.

0484