

# Chemsafe® Brands

## Product Specifications

Item A71689 (5 gal./pail)

Item A71690 (55 gal./drum)



### Product Description:

**Chemsafe 100 HP Low Odor Mastic/Adhesive Remover** is specifically formulated for use in the quick and efficient removal of asphaltic floor tile mastic. **Chemsafe 100 HP** is a High Performance version of **Chemsafe 100**, giving faster penetration and solvency than our lower cost **Chemsafe 100**. **Chemsafe 100 HP** is for use by contractors who have developed more production line type removal processes where removal time is optimized. This fast-acting emulsifiable solvent quickly dissolves floor tile mastic and is equally efficient in removing spray adhesive and natural pastes and glues on tough asbestos abatement jobs. The high penetrant content quickly softens the mastic (or adhesive) within minutes of complete saturation, and in many instances, can be completely liquefied using a squeegee or push broom. In addition, the special emulsifiers found in **Chemsafe 100 HP** assist in it's high rinsability.

- Low Odor
- $\geq 141^{\circ}\text{F}$  Flash Point
- Fast Acting / High Performance
- Emulsifiable

### Directions for Use:

Saturate mastic to be removed manually or a with garden sprayer. Allow time for remover to penetrate and soften mastic. Dislodge with stiff broom and/or squeegee, repeat if necessary. Thoroughly rinse, wash, and/or clean treated surface upon completion of job. Surface must be completely rinsed clean and allowed to dry before any replacement materials can be installed. Dispose of in accordance with federal, state and local regulations.

### Product Data:

General ID	Hydrocarbon Mixture	Vapor Pressure (mm hg)	<1
Odor	Light Solvent	Clean Up	Water & Detergent
Color	Clear Liquid	Reactivity	Stable
Flash Point	$\geq 141^{\circ}\text{F}$	Application	Manual or Airless
Coverage	75-100 sq. ft./gal	Shelf Life	1 Year
Vapor Density (air=1)	>1	Shipping Class	55
Solubility in Water	Emulsifies in water	Shipping Weight	5 gal. = 37 lbs. 55 gal. = 415 lbs.
Specific Gravity (water=1)	.8177	DOT Shipping Name	Combustible Liquid NOS
Percent Volatile	90-99	DOT Hazard Class	3, PG III, NA1993
Evaporation Rate (butyl acetate=1)	<1		
Boiling Range	>300 $^{\circ}\text{F}$		

*If shipped under 119 gallons per container, product has been certified by DOT as being NON-REGULATED.*

**DISTRIBUTED EXCLUSIVELY BY ARAMSCO, INC. :**

PHILADELPHIA (800) 767-6933    CHICAGO (800) 767 9981    HOUSTON (800) 767-8392    DALLAS (800) 767-5744    PHOENIX (800) 767-9372    NEW ORLEANS (866) 767-9180    CORPORATE-NEW JERSEY (800)767-6933

BOSTON (800) 767-1767    HARTFORD (800) 767-7731    NEW YORK CITY (888) 767-4359    SAN JUAN (787) 880-0335    LOS ANGELES (800) 767-4620    TAMPA (800) 767-1225    DURHAM (888) 941-6368    ROCHESTER-NY (800) 767-4101