

Chemsafe® Brands

Product Specifications

Item A68364 (5 gal./pail)

Item A68365 (55 gal./drum)



Product Description:

Chemsafe® 100C HP Low Odor Mastic/Adhesive Remover is a specifically formulated product developed by Chemsafe Brands for use in the quick and efficient removal of asphaltic floor tile mastic. Chemsafe® 100C HP is a CARB / OTC Compliant version of Chemsafe® 100 HP. Chemsafe® 100C HP is for use by contractors who have developed more production line type removal processes where removal time is optimized. This fast-acting emulsifiable solvent quickly dissolves floor tile mastic and is equally efficient in removing spray adhesive and natural pastes and glues on tough asbestos abatement jobs. The high penetrant content quickly softens the mastic (or adhesive) within minutes of complete saturation, and in many instances, can be completely liquefied using a squeegee or push broom. In addition, the special emulsifiers found in Chemsafe® 100C HP assist in it's high rinse ability.

- Low Odor
- ≥141°F Flash Point
- Fast Acting
- Emulsifiable
- CARB Compliant
- OTC Compliant

Directions for Use:

Saturate mastic to be removed manually or with a garden sprayer. Allow time for remover to penetrate and soften mastic. Dislodge with stiff broom and/or squeegee, repeat if necessary. Thoroughly rinse, wash, and/or clean treated surface upon completion of job. Surface must be completely rinsed clean and allowed to dry before any replacement materials can be installed. Dispose of in accordance with federal, state and local regulations.

Product Data:

General ID	Hydrocarbon Mixture	Vapor Pressure (mm hg)	CARB / OTC Compliant
Odor	Light Solvent	Clean Up	Water & Detergent
Color	Clear Liquid	Reactivity	Stable
Flash Point	≥141°F	Application	Manual or Airless
Coverage	75-100 sq. ft./gal	Shelf Life	1 Year
Vapor Density (air=1)	>1	Shipping Class	55
Solubility in Water	Emulsifies in water	Shipping Weight	5 gal. = 37 lbs. 55 gal. = 415 lbs.
Specific Gravity (water=1)	.8277	DOT Shipping Name	Combustible Liquid NOS
Percent Volatile	90-99	DOT Hazard Class	3, PG III, NA1993
Evaporation Rate (butyl acetate=1)	<1	<i>If shipped under 119 gallons per container, product has been certified by DOT as being NON-REGULATED.</i>	
Boiling Range	>300°F		

.....
DISTRIBUTED EXCLUSIVELY BY ARAMSCO, INC.

CORPORATE-NEW JERSEY
(800)767-6933

CHICAGO
(800) 767 9981

HOUSTON
(800) 767-8392

DALLAS
(800) 767-5744

PHOENIX
(800) 767-9372

NEW ORLEANS
(866) 767-9180

ROCHESTER-NY
(800) 767-4101

BOSTON
(800) 767-1767

HARTFORD
(800) 767-7731

NEW YORK CITY
(888) 767-4359

SAN JUAN
(787) 880-0335

LOS ANGELES
(800) 767-4620

TAMPA
(800) 767-1225

DURHAM
(888) 941-6368