

# Chemsafe® Brands

## Product Specifications



Item 57263 (5 gal./pail)  
Item 57261 (55 gal./drum)

### Product Description:

**Chemsafe 200 Extra Strength Mastic/Adhesive Remover** is a specially formulated product developed by **Chemsafe Brands** for use in the quick and efficient removal of asphaltic floor tile mastic. Not only does this fast-acting emulsifiable solvent quickly dissolve floor tile mastic, it is equally efficient in removing spray adhesive and natural pastes and glues on tough asbestos abatement jobs. The high penetrant content softens the mastic (or adhesive) within minutes of complete saturation, and in many instances, can be completely liquefied using a squeegee or push broom. In addition, the special emulsifiers found in **Chemsafe 200** assist in its high rinseability.

Our strongest mastic remover, **Chemsafe 200** is ideally suited for use in areas where a lower concentration low odor mastic remover will not work as effectively, and should not be used in occupied areas or areas where strong odors would be of concern.

- **Fast-acting**
- **≥141°F Flash Point**
- **Powerful**
- **Emulsifiable**

### Direction for Use:

Saturate mastic to be removed manually or with garden sprayer. Allow time for remover to penetrate and soften mastic. Dislodge with stiff broom and/or squeegee, repeat if necessary. Thoroughly rinse, wash, and/or clean treated surface upon completion of job. Surface must be completely rinsed clean and allowed to dry before any replacement materials can be installed. Dispose of in accordance with federal, state, and local regulations.

### Product Data:

General ID	Hydrocarbon Mixture
Odor	Mild to Mid-Range Solvent
Color	Clear Liquid
Flash Point	142°F - 150°F
Coverage	75-150 sq.ft./gal.
Vapor Density (air = 1)	> 1
Solubility in Water	Emulsifies in Water
Specific Gravity (water = 1)	.8077
Percent Volatile	93 - 99
Evaporation Rate (butyl acetate = 1)	< 1
Boiling Range	> 300°F

Vapor Pressure (mm hg)	< 2
Clean Up	Water & Detergent
Reactivity	Stable
Application	Manual or Airless
Shelf Life	1 Year
Shipping Class	55
Shipping Weight:	5 gal. = 37 lbs. 55 gal. = 415 lbs.
DOT Shipping Name:	Combustible Liquid NOS
DOT Hazard Class	3, PGIII, NA1993
<i>If shipped under 119 gallons per container product has been certified by DOT as being NON-REGULATED.</i>	

**DISTRIBUTED EXCLUSIVELY BY ARAMSCO, INC. :**

PHILADELPHIA (800) 767-6933	CHICAGO (800) 767 9981	HOUSTON (800) 767-8392	DALLAS (800) 767-5744	PHOENIX (800) 767-9372	NEW ORLEANS (866) 767-9180	CORPORATE-NEW JERSEY (800)767-6933	
BOSTON (800) 767-1767	HARTFORD (800) 767-7731	NEW YORK CITY (888) 767-4359	SAN JUAN (787) 880-0335	LOS ANGELES (800) 767-4620	TAMPA (800) 767-1225	DURHAM (888) 941-6368	ROCHESTER-NY (800) 767-4101