

Titan™ Stretch Lanyard w/Shock Absorber Pack

Description_____

Titan Stretch lanyards combine the integral SofStop® shock absorber with a unique stretchable lanyard design.

Materials_____

Webbing:

- Safety Strap: Type 7 webbing
- Safety Jacket: Tubular polyester

Thread: 6 cord bonded 3 strand polyester

SofStop Cover Vinyl

Label: Valeron

Hardware: Steel

Locking Snap Hooks: 5,000 lb (22kN).

* All hardware meets ASTM (50) fifty-hour salt spray test requirements.



T6121SS/6FT shown

Technical_____

- Locking Snap Hooks: 3/4 in. (19mm) opening
- Locking Rebar Hooks: 2 1/2 in. (63mm) opening
- Webbing: 5,000 lbs. (22kN)
- Thread: 42 lbs. (0.19kN)

SofStop® Pack Max Working Load Capacity

OSHA/ANSI: 310 lbs (141 kg)

CSA: 254 lbs. (115 kg)

Certification_____

OSHA 1926.502, 1910.66; ANSI A10.32 and CSA Z259.11

Elongation/Deceleration

Distance: 42 in. (107cm)

Fall Arrest Force: 900 lbs. max. (4kN)

<i>Model No.</i>	<i>No. of Legs</i>	<i>Harness Connection</i>	<i>Anchorage Connection</i>	<i>Lanyard Length</i>
<i>T6111SS/6FT</i>	One	Locking Snap Hook	Locking Snap Hook	6 ft. (1.8m)
<i>T6112SS/6FT</i>	One	Locking Snap Hook	Locking Rebar Hook	6 ft. (1.8m)
<i>T6121SS/6FT</i>	Two	Locking Snap Hook	Locking Snap Hook	6 ft. (1.8m)
<i>T6122SS/6FT</i>	Two	Locking Snap Hook	Locking Rebar Hook	6 ft. (1.8m)

Models are available in lengths from 4 ft. (1.2m) to 6 ft. (1.8m).

MILLER®

by Honeywell

Toll Free 800-873-5242 • Phone 814.432.2118 • Fax 814.437.2973 • www.millerfallprotection.com

▲ WARNING! THIS DOCUMENT PROVIDES AN OVERVIEW OF FALL PROTECTION PRODUCTS AVAILABLE FROM HONEYWELL AND CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE DATA. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. HONEYWELL RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO EACH USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.