

Syclone | LGR145 Dehumidifier

Outperforms the competitor's OEM dehu from 80/60 and up — plus pulls 300% more moisture in low-grain conditions.

- ▶ **Saves time** — convenient inlet and outlet temperature and RH monitoring
- ▶ **Large-capacity pump basin** holds water after a power outage or unexpected shut-down
- ▶ **Unit automatically restarts** after power failure
- ▶ **Ergonomic fold-down handle** and onboard hose and cord storage
- ▶ **Unsurpassed durability and reliability** — built tough to last
- ▶ **Digital display** with plain-language messages and built-in humidistat



Item	Description
53480	Syclone LGR145 XL Dehumidifier with Filter (ea)
Accessories	
55315	F368 Prefilter (3/pk)



SPECIFICATIONS

Model	Syclone LGR145
Power	9.8 amps, 115V
Water Removal AHAM (80°F/60%RH)	145 Pints 68.6 liters/day
Water Removal Max (Max. At Saturation)	235 Pints 111 liters/day
Process Air (Max.)	280 CFM 476 CMH. Floor-Level Outlet
Filter Type	3M HAF Filter 24 Pack F368 (Same As Drizair 1200)
Dimensions	33.5 x 20 x 20 in. 85 x 51 x 51 cm
Use Weight	115 lbs. 50 kg
Drain Hose	40 ft. 12.2 m
Power Cord	25 ft. 7.6 m
Construction	Durable Rotomolded Polyethylene Shell

PROUDLY
BUILT IN USA



Locations Nationwide

Atlanta | Baltimore | Boston | Chicago | Dallas | Detroit | Hartford
Houston | Los Angeles | Minneapolis | Nashville | New Orleans
New York City | Philadelphia | Phoenix | Puerto Rico
Raleigh-Durham | Rochester | Tampa

800.767.6933
www.aramSCO.com