

Phoenix Guardian HEPA System™

Performs Several Critical Air Quality Remediation Functions Simultaneously

The Phoenix Guardian HEPA System™ was the first portable air scrubbing device designed exclusively for the restoration industry. The Guardian can perform several critical air quality remediation functions simultaneously.

The Guardian HEPA System[™] captures virtually all removable airborne particles. The optional 4-stage absorption filter contains a blend of activated carbon and potassium permanganate to remove airborne odors and chemicals.


The true 1400 cfm capacity of the Phoenix Guardian HEPA System $^{\text{TM}}$ will perform one air change of a 12 x 14 foot room in less than a minute. In order to be effective, an air scrubber should be able to perform a minimum of four air changes per hour. Therefore, a single Guardian can be expected to control up to 21,000 cubic feet.

The Guardian's high airflow and multiple ducting options allow for the combination of negative or positive air flow control of an area and containment air scrubbing at the same time. This provides the unique ability to continually filter the indoor air and depressurize the damaged site to prevent the spread of contamination simultaneously.

The Guardian's intake will accept either 18" flex-duct or 12" flex-duct with the included adapter, to pressurize areas for protection from contamination or to draw contaminated air from areas that are difficult to access or too small to accommodate an air scrubbing device.

Every Guardian HEPA System™ comes with one 14" lay-flat duct ring, for 100% negative air operation, and two 10" lay-flat duct rings for a combination of negative air, air scrubbing or positive airflow.





The built-in manometer provides precise measurement of air-flow through the HEPA filter and aids in determination of HEPA filter replacement intervals.



Features

- 2-Speed operation (1400-900 CFM)
- Multiple ducting options
- · Built-in manometer
- Only 12 amps
- · Stainless steel cabinet
- · Optional fourth stage carbon filter
- Wheeled cart design





Phoenix Guardian HEPA System™

Specifications

Part No. 4024848

Power 12 amps, 110-120 VAC, Grounded

Blower 2-Speed

High: 1400 CFM* w/o external duct Low: 900 CFM* w/o external duct

Filters: 24" x 24"

1-stage 1" Spun Polyester 2-stage 2" Pleated Media 3-stage 12" V-bank HEPA

(optional) 4-stage 2" Carbon and Potassium Permanganate

Warranty One Year, 100% Parts and Labor

Dimensions

 Width
 25"
 29"

 Height
 39"
 45"

 Depth
 25"
 28"

 Weight
 121 lbs
 155 lbs

Popular Accessories And Replacement Filters

4024750 12" x 25' In-take Flex Duct 4023643 18" x 25' In-take Flex Duct 4024935 10" x 250' Lay-flat Duct 4024936 14" x 250' Lay-flat Duct 4023374 24" x 24" x 1' Polyester Pre-Filter 4023375 24" x 24" x 2" Pleated Pre-Filter 4023244 24" x 24" x 12" V-Bank HEPA Filter 4023487 24" x 24" x 2" Carbon Filter 24" x 24" x 2" Carbon Filter Frame 4024764 4024440 Kestrel 3000 Multi-Meter 4024528 Carbon/Potassium Permanganate media, five-gallon bucket (30 lbs)

ETL Listed



*Delivered air flow w/3-stage clean filter operation.



4201 Lien Rd Madison, WI 53704 608-237-8400 1-800-533-7533

Multiple Ducting Options For Intake and Exhaust










Optional Activated Carbon & Potassium Permanganate Filtration

The Guardian Carbon Filter Frames are an improved way to provide gas and odor filtration. The 20-gauge galvanized metal frames are available in 24" x 24" x 2" (Part No. 4024764) for the Guardian HEPA System™. The Carbon and Potassium Permanganate media to fill the frames is available in 30 pound buckets (Part No. 4024528).

There are several advantages to using the Carbon Filter Frames instead of manufactured carbon filters:

- The media will stay "fresher" stored in the 5 gallon bucket.
- Loading the filter by the job provides the opportunity to adjust the amount of media for the specific job.
- Substantial savings are realized by using the filter frame over manufactured carbon filters.
- Replacement foam liners and honeycomb inserts are also available.



TS-121 Therma-Stor LLC 04/10 Specifications subject to change without notice.