

# Series 356U — 0 - 1200 PSI

<b>Inlets:</b>	3/8 (F) NPT (2)
<b>Outlets:</b>	3/8 (F) NPT (2)
<b>MAX RPM:</b>	1750
<b>MAX PSI:</b>	1200
<b>MAX GPM:</b>	3.0
<b>MAX Temp:</b>	140°F
<b>SEALS:</b>	NBR
<b>Body</b>	Anodized Aluminum
<b>Plunger</b>	Stainless Steel
<b>Valves</b>	Stainless Steel
<b>Fasteners</b>	Stainless Steel



356U/M64

## 120 volt pump and motor sets

PN	Model	PSI Spray	Nozzle Size	GPM Spray	AMPS Spray	Weight (lbs.)
80011	356U-190/M64	1200	'04	2.2	15	48
80711	356U-200/M64	1000	'045	2.3	15	48
80712	356U-230/M64	800	'06	2.7	15	48

## 230 volt - 50/60 Hz pump and motor sets

PN	Model	PSI Spray	Nozzle Size	GPM Spray	AMPS Spray	Weight (lbs.)
80712+	356U-230/M64	1200	'04	2.2	7.5	48
80711+	356U-200/M64	800	'03	1.8	6.0	48

+ Motor 120/230V, 50/60 Hz. Must be wired by customer for 230V. Note: Performance for 50 Hz. Consult Pumpteck for applications with 60 Hz.



## Hard Surface Pump Set

- **Hard surface cleaner with your extractor**
- **Affordable and durable**
- **Plugs into any 15 amp outlet**

PN	Model	PSI Spray	Nozzle Size	GPM Spray	AMPS Spray	Weight (lbs.)
80346	Hard Surface Pump Set	1200	'04	2.2	15	56