

Introducing the

zip DOOR™



Seal any doorway in
under a minute.

REUSABLE

ZipDoor™

The ZipDoor™ is available for standard and commercial doors



The new ZipDoor kit is a great way to create a dust barrier when all you need to seal is the doorway. One person can install it in under a minute.

You'll save hours on jobs with lots of doors like commercial office space, hotels, hospitals, and more. The savings can really add up.

The ZipDoor kit is also great for residential jobs. Use it for kitchen and bath remodeling, or for sectioning off any work area. And, the ZipDoor makes it easy to meet the EPA's RRP requirement for a covered doorway.

- Pays for itself in time savings
- For standard doors, up to 3' x 7'
- For commercial doors up to 4' x 8'
- Made from 4 mil plastic sheeting (commercial unit is flame retardant)
- Two heavy duty zippers pre-installed
- Includes new ZipWall® double-sided tape
- Can be repositioned easily for up to 1 hour
- Ideal for EPA RRP rule use

Attaching the ZipDoor™ is easy.

Attaching the ZipDoor to any door frame is a snap. Just follow these simple steps and you'll be done in less than a minute.

Test ZipWall® Tape compatibility on a surface that will not be visible before applying it to the doorway.

Another innovative dust control product by **ZIPWALL®**



1 Clean dust from surface of doorway.



2 Apply ZipWall® Tape at the top of the doorway. The low-tack adhesive faces paint, high-tack adhesive is covered by red release-paper.



3 Remove red release-paper.



4 Apply ZipWall® Tape to the left and right sides of the doorway. **Be sure to overlap with tape at the top to create a continuous seal around the door.** Then remove the red release-paper.



5 Holding the ZipDoor sheet at the top, place it so the sheet is centered on the doorway. **Important: Leave two to three inches of sheeting to overlap at the floor.** This limits dust from coming under the door. Press sheet against tape.

The ZipDoor sheet may be repositioned easily for the first few minutes. A full-strength bond will occur after about an hour.



6 Install the enclosed Flap Hooks for holding up the door flap when easy access is needed. On the back of the flap, poke the short end of the hooks through the plastic sheeting just below the top of the doorway and let them hang there ready for use.



7 To remove: Carefully peel the tape and plastic off the doorframe. To minimize paint damage pull the tape off slowly.

Note: ZipWall® Tape is rated for 14 day use.

8 To reuse: carefully peel the tape off the ZipDoor. When you are ready to use the ZipDoor again, use only genuine ZipWall double-sided tape.

For more information call 800 718 2255 or visit us at www.zipwall.com



ZipWall[®] tape

Our new ZipWall tape was designed for use with the ZipDoor kit, but it is also ideal for putting a barrier over built-ins, cabinets or furniture that can't be moved. One side of ZipWall tape is gentle on painted surfaces like traditional painter's tape. The other side has an adhesive specially designed to hold plastic sheeting.

ZipWall tape is available in two sizes:

1" x 20 yards *and* 2" x 20 yards

ONE *It's always a good idea to do a test before*
TIP: *applying tape to any finished surface.*

ZIPWALL[®]

1 800 718 2255 • www.zipwall.com