



VIPER

GROUT & CONCRETE SEALER

Resists Soils, Stains & Efflorescence • Vapor Permeable

Part # CH05GL

X Grout X Concrete X Quarry Tile X Saltillo

X = Primary Use ✓ = Secondary Use



VIPER GROUT & CONCRETE SEALER utilizes a unique formula to achieve all the benefits of solvent-based grout sealers in a water based product. It resists soils, stains, chemical degradation, biological growth, and even efflorescence. It offers excellent oil and water repellency and hold-out. Yet, Grout & Concrete Sealer is vapor permeable so it lets water vapor out but resists letting water in!

This is a very affordable product that is outstanding on grout & concrete and can be used on any other porous tile such as quarry or Saltillo. It provides exceptional protection at a price point you and your customers will love.

- Cost effective and perfect for sealing grout and concrete
- Water based sealer that is safe and effective
- Protects grout and concrete against unsightly spills and stains
- Vapor permeable

DIRECTIONS:

Cleaning is necessary

Surface must be cleaned and thoroughly rinsed. The drier the grout and floor surface the better the penetration. Make sure that there are no puddles in grout lines and use air movers to speed the drying of the floor surface and grout lines before application.

Dilution Instructions

Do not dilute; ready to use. Coverage should be between 600 to 1200 sq. ft. per gallon depending on the porosity of the surfaces and

the coverage required (grout only or entire surface).

Application Methods

Apply to grout lines. When dry (typically 1 to 2 hours) if there is a visual residue on tiles, then wipe off with hot water. For entire floor application, apply sealer with choice of applicator. A second coat may be necessary after 1 hour. Place drop of sealer on newly sealed grout or floor surface and see if it absorbs into grout or floor surface. If it does absorb readily, then a second coat is necessary. Test for suitability in an inconspicuous area, especially

for polished marble and extremely porous surfaces.

Post Application

Precautions

Floor is typically walkable in 3 to 4 hours, ready for use after 8 to 12 hours, and completely cured in 24 hours. These times will be less if only grout was sealed. After 6 to 18 months, reapplication may be necessary, depending upon the traffic and the type of surface sealed.

RTU ph - 7.5

Available in Gallons and 4 x 1 gallon cases

Hydro-Force | 4282 South 590 West Salt Lake City, UT 84123

www.hydroforce.com • (800)-637-3789

See Material Safety Data Sheet at www.hydroforce.com/msds for safety and regulatory information.

by **HF** **HYDRO-FORCE™**

