



FIRE POWER

Heavy Duty Cleaner Wall Wash/General Purpose Degreasing

Contents: One U.S. Gallon (3.79 Litres)

11.5 RTU pH



- **Fire Power is ideally suited for cleaning smoke residues off painted walls, paneling and wall coverings.**
- **Simply by diluting Fire Power to the needed strength, all levels of soiling can be removed from hard surfaces that are safe with water.**
- **Fire Power is a hard hitting blend of surfactants, alkaline builders, and solvents.**
- **Utilizes two hard hitting ingredients from FLEX Powder which provide the appropriate alkalinity.**
- **Includes a dynamic degreasing trio of surfactants with low levels of foam.**
- **One of the surfactants has a slight cationic charge to draw particulate soils like soot into suspension.**

DIRECTIONS

Remove loose soil or soot with dry cloth or dry cleaning sponge prior to cleaning. Dilute 1 part Fire Power to 4 parts water for extreme situations. Adjust dilution according to difficulty of job. Spray or wipe on diluted Fire Power. Wipe off and rinse with wet cloth. Clean in arm width sections from the bottom up. Rinse from the top down.

Add 4 oz. of Smoke & More per ready to use gallon to neutralize smoke odor while cleaning.

For woodwork, venetian blinds, plastic, vinyl, etc. dilute 1 part Fire Power to 64 parts water.

For general hard surface cleaning, like cement or concrete, dilute 1 part Fire Power to 32 parts water.

Available in Gallons and 4 x 1 gallon cases | Dilution Ratio: 2-4 oz./gal.

OmniPro Manufacturing | 4282 South 590 West Salt Lake City, UT 84123 | 866-215-7591

