



REVIVE

STONE COLOR ENHANCER & SEALER



Revives Stones Appearance Back To "Like New"



CST22GL

RTU pH=4.0

Revive Stone Color Enhancer and Sealer is designed to reveal the vibrant colors hidden in the stone and highlight all the rich colors of the stone. Revive Color Stone Enhancer is designed for use on natural stone such as limestone, slate, travertine, sandstone, flagstone, tumbled stone, flamed stone & textured stone. Revive will rejuvenate and revitalize the appearance of almost any interior stone floor or surface. It is ideally designed for porous, unpolished stone and saltillo tile. It's easy-to-use water based formula provides standard protection against most spills and stains.

Revive Stone Color Enhancer and Sealer may also be used to disguise minor etching and scratching in polished stone surfaces.

- Revives and brings out the natural color and beauty of stone and seals it against spills and soiling
- Can disguise minor etching and scratching
- Keep from freezing, not freeze-thaw stable
- Rejuvenate and revitalize stone
- Ideal for porous, unpolished stone, slate, and saltillo tile

TRANSFORM / MODIFY

Directions:

Read entire label before using. Use only as directed. Test in a small inconspicuous area with a 24-hour cure time to determine ease of application and desired results. Allow new grout installations to cure for at least 72 hours prior to application. Be sure surface is clean, thoroughly dry and free of sealers, waxes and coatings. Not recommended for exterior surfaces.

1. Shake vigorously before each use..
2. Apply a thin, even coat of Revive using a paint pad, roller or brush. For larger areas, Revive can be applied by pouring or spraying using a low-pressure sprayer, and spreading with a clean synthetic bristled brush. Avoid applying product on surfaces on which it is not intended to be used. Do not aerosolize this product.
3. Allow product to penetrate the surface for 15-30 minutes; denser material may require maximum time for Revive to penetrate. Keep surface wet with sealer, adding more product if needed to prevent

dry spots, for the entire penetration time. Following penetration time, completely wipe surface clean and dry with absorbent towels. For larger areas, buff the surface using a rotary floor machine and white pad. **DO NOT ALLOW EXCESS REVIVE TO DRY COMPLETELY ON SURFACE.**

4. A second coat may be needed for porous, absorbent surfaces or if a darker appearance is required. Apply second coat no sooner than 1 hour after first coat following directions in steps 1-3. Clean tools used during application with water.
5. A full cure is achieved after 24-72 hours; foot traffic may begin in 6-8 hours.
6. For use to disguise minor etching or scratching on polished stone surfaces, apply solution to cloth and rub into etch mark. A second coat may be necessary. After second application, if etch is still visible, polishing will need to be performed to eliminate etch.

