



Wood Cleaner

Restorative Cleaner



Wood Cleaner contains no oils or waxes that attract and hold soil. It also has a fresh scent to please you and your customer. Wood Cleaner is an excellent everyday cleaner that the homeowners can use (in dilution) for damp-mopping their newly restored hardwood floors.

Do not use Hydro-Force's Wood Cleaner for two weeks on a newly finished surface. Hydro-Force Wood Cleaner can be used with a low speed buffer and white buffing pad for mechanically cleaning wood floor.

Instructions

It is recommended that you clean an area of approximately 10 Sq. Ft. at a time.

For restoration cleaning and wood finishing:

Mix 8 parts water to 1 part Wood Cleaner (2 ounces of Wood Cleaner in the sprayer and add 16 ounces of water). Spray a light application on the hardwood floor area being restored. With a low speed floor machine (175 rpm) scrub the floor with a 3M maroon pad or equivalent. It is best to place a white buffing pad between the maroon pad and the driver block to offer cushioning and prevent any damage to the floor. Be careful not to over-apply Wood Cleaner as excess water on the floor can cause damage. The scrubbing action will loosen and remove soil build-up as well as the surface of the old finish, leaving a surface that has a slightly rough feel. This new surface will more readily accept and bond to the Hydro-Force Wood Finish.

Mop the floor with a Hydro-Force Wood Finish Applicator to absorb the Wood Cleaner and the released soil. Repeat this mopping procedure a second time. Finally, spray the floor with a light coat of wood cleaner and buff the floor with your floor machine and a cotton bonnet (absorbent pad). While wearing shoe covers, go over the floor a final time with a damp clean terry cloth cover attached to the applicator. This will remove any dust or lint before applying finish. With this final procedure, you are now ready to

apply Hydro-Force Wood Finish as soon as the floor is dry.

In corners and along the edges of the floor you will need to accomplish the above procedures by hand. You may remove the center portion of the maroon pad or use a "Scotchbrite" scrubbing pad for this handwork.

For continual maintenance:

Mix a solution of 1 part Wood Cleaner to 8 parts water in a sprayer. Spray a light coat of the solution on the floor. Dampen the fitted pad on your Hydro-Force Applicator and agitate the solution on the floor to loosen the dirt. Mop the floor with a clean fitted pad to remove additional soil - this will provide a fresh clean look to the surface.

Directions for cabinets and hardwood furniture: The same procedures apply for cabinets and furniture as for floors except the cleaning is done by hand. Instead of the rotary machine and maroon pad, use your hand and the center portion of maroon pad or a Scotchbrite hand pad.

Removing the soil and surface finish is done with a damp terry cloth towel or one of your applicator terry cloth pads.

Continual maintenance of cabinets and furniture is the same as for floors except that it is done by hand and it will not be required as frequently.



Available in gallon bottles and 4 x 1 gallon cases

Part # CW025GL

Hydro-Force | 4282 South 590 West Salt Lake City, UT 84123

www.hydroforce.com • (800)-948-1779

See Material Safety Data Sheet at www.hydroforce.com/msds for safety and regulatory information.