



Wood Finish

Wood Finish - Semi-Gloss



Under normal residential conditions a wood floor should be cleaned and refinished with two coats of Hydro-Force Wood Finish at least every two years. It should be done each year under heavy traffic conditions. Hydro-Force Wood Finish should not be used as a primary finish. If floors are either new or must be sanded down to bare wood, Hydro-Force Wood Finish should not be used. Use it only as a maintenance topcoat where an existing primary coat of quality finish has already been applied.

Instructions

- 1. Clean:** Before finishing a floor or other hardwood surface first clean surface with Hydro-Force Wood cleaner. Scrub the surface with a maroon pad or equivalent to remove soil, damaged finish and to affect a slight amount of abrasion that allows Hydro-Force Wood Finish to adhere to the surface. Follow the directions on the Wood Cleaner Label. More details may be found in the Hydro-Force Wood Products Training Manual.
- 2. Repair Damaged Areas:** Repair scratches, gouges or other damage to the wood surface with Hydro-Force Wood Patch. Refer to the Wood Products training manual and video for directions.
- 3. Finish the Hardwood Surface:** Once the floor or other surface is properly prepared, it is ready to be finished with Hydro-Force Wood Finish. Shake well before each use. For floors, pour a pool of the product about the size of a saucer on the floor. Spread the finish in an even coat over the floor with the Hydro-Force Applicator and fitted terry-cloth pad. Continue to pour and spread the product until an even coating has been applied over the entire area. Allow at least 30 minutes for drying and apply another coat in the same fashion. You may judge drying visually. Allow about 10 additional minutes for drying after the surface appears dry.

Cabinets and Furniture Surface: Apply finish with a soft lint free cloth. Use latex or rubber gloves to keep finish from bonding to hands. Finish should be applied in a lighter coat than is needed for a floor application. A third coat of finish may be needed for an acceptable appearance.

Fire and Water Damage Restoration: Hydro-Force's Wood Finish is a greater sealer/finish to use after a fire or smoke damage, sealing in odors while adding a new protective finish. Hydro-Force's Wood Finish can be used after water losses to restore small surface checks while adding a new surface finish. Clean floor, cabinets and furniture with your normal restoration cleaners. A final surface cleaning is needed with Hydro-Force Wood Cleaner to neutralize and prep the surface. Apply finish as directed above.

Coverage:
Approximately 1,000 sq. feet per gallon.

- The floor may be walked on without shoes after drying for 1 - 2 hours.
- Furniture may be replaced after 24 hours. Rugs may be replaced after three days.



Available in gallon bottles and 4 x 1 gallon cases

Part # CW032GL

Hydro-Force | 4282 South 590 West Salt Lake City, UT 84123

www.hydroforce.com • (800)-948-1779

See Material Safety Data Sheet at www.hydroforce.com/msds for safety and regulatory information.