



Hottest, Most Powerful Truckmount Ever!

The Titan 875 offers top-of-the-line performance that's perfect for large commercial and residential jobs as well as for water damage restoration. Crew applications are a cinch because you can simultaneously operate up to three wands with the optional 2.5" adapter kit. The powerful solution pump provides up to 5.5 gallons per minute of water flow at temperatures as high as 270° F. It also provides non-heated pressure washing at 3,000 psi. If you want the biggest and the baddest, the Titan 875 is your truckmount.

In addition to superior performance, reliability and flexibility, the 875 earns "thumbs up" for its serviceability. Keeping the needs of owner/operators in mind has been the highest priority for HydraMaster, giving you better performance by design. With the Titan's magnetic side panels that are easily removed with no tools necessary, routine maintenance can now be "routine."

Key Features:

- 3,000 psi
- Triple wand capable (optional kit required)
- High, consistent working temperatures up to 270°F
- Easy maintenance, high reliability

Standard Equipment

- Runtime hour meter
- Chemical flow meter (0-10 gph)
- Chemical flow control valve
- 5 gallon chemical jug
- Vacuum gauge (0-30" Hg)
- Solution pressure gauge (0-1,500 psi)
- Solution pressure adjustment
- Pre-wired pump-in switch
- Pre-wired APO Switch
- Fresh water inlet
- Water system drain valve
- Stainless steel carpet cleaning wand
- Diverter valve (with ADC heat control)
- Diverter/clutch package for flood work
- Electronic throttle control
- Electrical circuit protection
- Pump clutch switch
- Solution temperature control selector
- Three solution outlets
- Solution Hose Length: 150 ft x 1/4"
- Vacuum Hose Length: 150 ft x 2"
- Wand Whip Line: 10 ft 1-1/2"
- 50 ft water supply line
- Recovery Tank: 100 gallon MaxxAir™
- Battery box
- Van installation kit
- Operation & maintenance manual
- Embroidered HydraMaster jacket



Learn more, scan here



GM® Vortec™ Engine:

- 61 HP, GM Vortec, 4 cylinder
- Fuel injected
- Three speed operation
- Cast iron block
- Fully liquid cooled
- Keyless ignition



5009 Competitor™ Tri-Lobe Blower

- 750+ cfm
- Low vibration-pulsation and sound reduction
- No grease fittings, dual oil bath lubrication
- Oil level sight windows



High Pressure Pump:

- 3,000 PSI unheated pressure
- 5.5 gpm volume
- 1,200 heated pressure
- Electric clutch control



Optional Equipment:

- 2.5" third wand adaptor kit - with a plumbed 2.5" connection included on the machine, the optional 2.5" adapter kit allows triple wand capability.
- High pressure kit - high pressure hose and high pressure wand
- Dura-Flow™ APO (auto pump-out)

Machine Specifications:

- Dimensions: 28"W x 42"H x 47"D
- Weight: 1,187 lbs
- Ignition: Electric keyless start
- Chemical System: Stainless steel last-step chemical injection, meter controlled
- Heating System: Tube and fin heat exchanger with ADC temperature control, max. temp. 270°F
- Wand Capacity: Triple
- Fuel Consumption: 1.7 gph
- Uses: Residential and Large Commercial