



Pressure Wash with Heat at 2,500 psi

The compact Boxxer 323HP offers twice the power of other machines its size, so jobs get done faster with a lot less work. Designed for residential and commercial jobs, it provides up to 210°F of temperature! You can also do heated pressure washing at up to 2,500 psi! The maintenance-friendly design includes glass sights to monitor oil levels. Our unique last-step chemical injection system eliminates chemical buildup in the pump and heat exchanger.

Key Features:

- Pressure wash with heat up to 2,500 psi
- Compact, road-tested design
- Superior hard surface cleaning
- High, consistent working temperatures up to 210°F
- Easy maintenance, high reliability

Standard Equipment:

- Runtime hour meter
- Chemical flow meter (0-10 gph)
- Chemical flow control valve
- 5 gallon chemical jug
- Vacuum gauge (0-30" Hg)
- Solution pressure gauge (0-1,500 psi)
- Solution pressure adjustment
- Pre-wired pump-in switch
- Pre-wired APO Switch
- Fresh water inlet
- Water system drain valve
- Stainless steel carpet cleaning wand
- Engine choke
- Engine throttle
- Electrical circuit protection
- Solution temperature control selector
- Solution Hose Length: 100 ft x 1/4"
- Vacuum Hose Length: 100 ft x 2"
- Wand Whip Line: 10 ft 1-1/2"
- 50 ft water supply line
- Recovery Tank: 70 gallon MaxxAir™ recovery tank
- Battery box
- Van installation kit
- Operation & maintenance manual
- Embroidered HydraMaster jacket



Learn more, scan here



Briggs & Stratton® Vanguard™ Engine:



- Fuel-efficient 23 HP engine, 1.0 GPH
- Reliable 2 cylinder OHV design
- Fuel efficient
- Keyed ignition
- Easy maintenance

Competitor™ SL 3006 Blower



- Hardened, precision helical gears
- Double-row ball bearings at gear end
- Precision machined ductile iron rotors
- Dual oil bath design with oil level sight windows

High Pressure Pump:



- 4.0 gpm capacity, tri-plunger pump
- Operating pressure, 0 to 2,500 psi
- Clean carpet, hard surfaces and pressure wash

Optional Equipment:

- Dura-Flow™ APO (auto pump-out) is externally mounted for easy service, no filters required
- RX-20™ rotary extraction tool
- DriMaster™ 2 upholstery tool
- Rotomolded 85 gallon fresh water tank
- Thru-floor exhaust kit

Machine Specifications:

- Dimensions: 24"W x 31.5"H x 35"D
- Weight: 535 lbs
- Ignition: Electric key start
- Chemical System: last-step chemical injection, meter controlled
- Heating System: Finned tube heat exchanger with stainless steel tubes. 210°F
- Wand Capacity: Single
- Fuel Consumption: 1.0 gph
- Uses: Residential and Light Commercial