

# Introducing

# BOXXER XL



You get uncompromising performance in a high-level, dual wand power-packed truckmount from the Boxxer XL. Incorporating time tested "best concepts" in design and engineering provides built-in reliability. Yet the Boxxer XL provides innovative and industry-first features that place it on a level previously unachieved for a machine in its class. Utilizing the HydraMaster Water Conservation System, it can be inactive under a full vacuum load for as long as 40 minutes without wasting fresh water. Whether you are setting up for carpet cleaning, or doing water extraction on a flood job, the "no-dump"/full bypass heat exchanger system means your hot water is used on the job, not dumped into the recovery tank, saving precious fuel every day.

The Boxxer XL also sets a new standard for quieter operation due to innovative concepts and design in routing and controlling the flow of blower air and exhaust gas. The Boxxer XL produces a decibel level of 68dB (at industry standard measurements of 12" Hg, 1.6 gpm water flow with closed doors). This is equivalent to the noise level previously only available with clutch drive, direct drive systems. The Boxxer XL is 20% quieter than a comparable slide-in truckmount.

Finally, the Boxxer XL produces performance levels that most truckmounts only dream about – True dual wand capabilities; 400+CFM (static measurement), attains 245°F temperature (185°F continuous flow at 1.25 gpm); and proven and tested coupler direct driven blower. A time tested and proven frame and drive system reduces vibration and wear on componentry. Accessibility and serviceability with removable magnetic panels makes maintenance a breeze.

## 31 HP + 400+ CFM + 1200 psi hot + 245° F

### Key Features:

- XS Footprint - More space in your van
- XS Noise - 68 dB, 20% quieter than comparable slide-ins
- XS Water use - HydraMaster water conservation system
- Best price point for its class
- Easy Maintenance, high reliability

### Applications:

- Residential, Large Commercial Carpet Cleaning
- Pressure Washing with full waste recovery capabilities
- Upholstery Cleaning
- Stone, Tile and Grout Cleaning
- Hard surface high pressure cleaning

### Machine Specifications:

- Dimensions: 24"W x 39"H x 41"D
- Weight: 800 lbs
- Ignition: Electric key start
- Chemical System: last-step chemical injection, meter controlled
- Heating System: Full divert tube and finned tube heat exchanger 245°F
- Wand Capacity: Dual



### Briggs & Stratton® Vanguard™ Engine:

- Fuel-efficient 31 HP engine, 1.6 GPH
- Fuel efficient
- Keyed ignition
- Easy maintenance



### 4007 Dominator™ Tri-Lobe Blower

- HydraMaster exclusive design
- Dual oil bath design with sight level windows
- Durable helical gear drive



### High Pressure Pump:

- 1,200 psi unheated pressure
- 4.0 gpm volume
- 1,200 psi heated pressure

